

**FIRST RE-ESTABLISHMENT****SPECIAL CORNER****DLC66ENE****GCDB 865100**

East-Northeast corner to Donation Land Claim No. 66, identical with the "L" corner of Donation Land Claim No. 65, located in Section 26, Township 38 South, Range 1 West, W.M.

Found 7 inches deep, ¼ x 1 x 15-inch iron bar, with 7 inches length of 1½-inch (outside) diameter steel spring centered on said bar. This monument reported on Survey Nos. 2766, 3059 and 4525.

To perpetuate this location, replace the above with and deposit it alongside a 1 x 36-inch Galvanized iron pipe, set flush, with yellow plastic cap marked: "JACKSON C.S."

Mound stones around corner and take new references:

- Fruit tree, 14-inch diameter (not scribed) bears N83°11'E, 147.15 feet to center of tree near base.
- English Walnut, 17-inch diameter, bark scribed "CS" bears N51°33'W, 35.95 feet to center of tree near base.
- A ¾-inch diameter iron pipe reported to be the S.E. corner of DLC 63, bears S89°27'50"W, 175.03 feet.

Corner lies S55°33'W, 10.5 feet from 4-inch diameter yew-wood post, being the most westerly post of (new) East bearing fence line and about 9½ feet South of location marker.

January 29, 1985  
E. McGinty  
R. Frost

Edward McGinty  
County Surveyor

P. 127-128

**ADDENDUM:**

Corner is located under a North - South bearing barbed wire fence line, 10 feet East of an irrigation ditch, 9 feet North of an 8-foot high fence post (corner of East and South bearing fence line around vineyard, and 9½ feet South of location tag on 8-inch x 8-inch railroad tie fence post.

S. Beecher 7/3/01