

FIRST RE-ESTABLISHMENT

DLC67ESE

GCDB 867130

East Southeast corner to DLC #67, Township 38 South, Range 1 West.

Found $\frac{3}{4}$ " pipe for corner which pipe was identified by Byron Keith whom has known this corner for 25 years which corner was pointed out to him by an old settler.

Also found remains of pine roots to the north- east and Black Oak roots to the southwest which corresponds to the official record BTs.

- Set a $1\frac{1}{2}$ " x 34" galvanized iron pipe 34" in the ground, for corner from which a 10" White Oak scribed CS-BT bears S47°W, 81.9 feet.
- The Northeast corner at the concrete foundation at the northeast corner of a garage bears S3°W, 198.1 feet.
- Set a $\frac{1}{2}$ " x 18" iron pipe which bears East 20.0 feet.

March 2, 1946
C. Z. Boyden
C. W. Bentley
Byron Keith, Present

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

DLC67ESE

GCDB 867130

East Southeast corner to DLC No. 67, located in Section 35, Township 38 South, Range 1 West, W.M.

Found 7 inches below the asphalt surface of Rapp Lane, in concrete, 3-inch diameter brass cap (not of record) marked:

T38S R1W
ESE | DLC
67 |
C.S.
1972

References set on First re-establishment in 1946 found:

- The Northeast corner, of the concrete foundation of garage, bears S3°W, 198.0 feet. Record: 198.1 feet.
- White Oak, 21-inch diameter, with healed blazes, bears S47°W, 82.0 feet to center of tree at lower blaze. Record: 81.9 feet.

Take new reference:

- Rebar, 5/8 x 24 inches, set 22 inches in the ground with yellow plastic cap marked: "JACKSON C.S." bears N88°32'E, 23.25 feet.
- A found 3/4-inch diameter iron pipe reported on Survey No's. 4778 and 4989, projecting 2 inches in East-West fence line, bears S88°32'W, 59.00 feet.

Corner lies on (projected) East-West fence lines along North side of asphalt road c. East-West and in the middle of Rapp Lane C. North.

October 8, 1984
E. McGinty
R. Frost

Edward McGinty
County Surveyor

V = 19°
P. -109

SEE NEXT PAGE FOR THIRD RE-ESTABLISHMENT

THIRD RE-ESTABLISHMENT


DLC67ESE

GCDB 867130

East Southeast of Donation Land Claim No. 67, located in Section 35, Township 38 South, Range 1 West, W.M.

Found 7 inches deep set in concrete, the 3-inch diameter brass cap set in 1972 which is found in field book marked "Corners Re-monumented for Triangulation Nets," page 6.

Over found monument set flush with surface of road, a 2½-inch diameter brass cap set in concrete marked:



References described on Second re-establishment dated 1984 found:

- White Oak, 23-inch diameter, with healed blazes bears S46°50'W, 81.90 feet to center of tree at lower blaze. Record: S47°W, 82.0 feet.
- 5/8-inch diameter rebar with yellow plastic cap marked "Jackson CS" brs, N88°32'E, 23.35 feet. Record: 23.25 feet.
- All other references now gone except the NE corner of garage which is not visible due to landscaping.

Set new references: 5/8 x 24-inch diameter rebar with aluminum caps set flush marked "Jackson County CS":

- Bears S40°21'26"E, 36.34 feet which is 2 feet north of east-west fence.
- Bears N41°21'15"W, 27.47 feet which is 1 foot north of power pole.

Corner lies in paved road which is at the south end of Rapp Lane where there are 4 other roads branching off to the NE, East, SW and West.

June 19, 1998
T. Newcomb
J. Burgess

Roger Roberts
County Surveyor

P. -14