

FIRST RE-ESTABLISHMENT

DLC67NW

GCDB 867110

Northwest corner DLC #67, Township 38 South, Range 1 West, W.M.

Found corner marked by stone. The remains of a 30" Yellow Pine stump bears S27°W, 41 links, and the remains of a White Oak stump S51°E, 34 links.

Set a ½" gas pipe 18" long, driven flush with the ground, 20 feet South on the West line of the claim for a reference point.

February 3, 1913
A. T. Brown,
Deputy County Surveyor

C.D. Runyon, Chainman
M. B. Kellogg, Chainman

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

DLC67NW

GCDB 867110

Northwest corner of DLC #67, Township 38 South, Range 1 West, W.M.

Found a ½" iron pipe for corner and a ½" reference pipe which bears South 19.83 feet. Also found the remains of the original Pine BT to the Southwest.

Set a 1½" x 25" steel tube with the ½" pipe inside the steel tube 6" below the surface of the county road for corner.

From which:

A 9" Black Oak scribed CS-BT which bears N65°E, 59.9 feet.

Scribe a 6" Black Oak being the most Northerly Oak of a cluster of three Black Oaks which bears N71½°W, 76.4 feet.

A ¾" iron pipe in a pyramid of concrete being an 8" top and a 12" base and 12" high bears S54°W, 151.6 feet.

November 13, 1953

C. Z. Boyden

L. D. Pinkham

Tom Furnas

SEE NEXT PAGE FOR THIRD RE-ESTABLISHMENT

THIRD RE-ESTABLISHMENT

DLC67NW

GCDB 867110

Northwest corner Donation Land Claim #67, Township 38 South, Range 1 West, W.M.

Found the 1½" steel tube with ½" iron pipe inside, 5" deep, as set for the corner on the Second Re-establishment on November 13, 1953.

Replaced said 1½" steel tube and ½" pipe with a 3" bronze disk, set in a 20" diameter x 14" deep concrete base, 8" deep in a monument case, stamped:

JACKSON COUNTY
T38S R1W
NW | DLC
Cor. | 67
1970
CONTROL MONUMENT

From which:

The ½" gas pipe bears S0°14'W, 19.90 feet (First Re-establishment Record of 1913: South 20 feet. 1953 Record: South 19.83 feet);

A 14" Black Oak, the most westerly one in a group of three, bears N65°06'E, 60.2 feet to center of the tree. (1953 Record: 9" Black Oak, N65°E, 59.9 feet).

Found a ⅝" rebar, flush with northerly edge of pavement, which bears N87°09'W, 223.20 feet.

March 27, 1972
Lloyd Shreeve
Ray Webber

Approved by:
Mark E. Boyden
County Surveyor

SEE NEXT PAGE FOR FOURTH RE-ESTABLISHMENT

FOURTH RE-ESTABLISHMENT

DLC67NW

GCDB 867110

Northwest corner to DLC No. 67, located in Section 34, Township 38 South, Range 1 West, W.M.

Found the center punched brass cap (set and described on Third Re-establishment dated 1972) in concrete, 8 inches deep in monument case.

References reported in 1972 found:

The Westerly branch, 22-inch diameter of a triple Black Oak, with healed blazes, bears Record: N65°06'E, 60.2 feet to center of said branch at upper blaze.

Gas pipe ½-inch diameter, found flush at the corner of South and West fence lines, bears S0°12'W, 19.95 feet. Record: S0°14'W, 19.95 feet.

Take new references:

Rebar 5/8 x 30 inches set 2 inches deep with yellow plastic cap marked JACKSON C.S., bears S50°33'E, 40.36 feet.

Black Oak, 11-inch diameter, marked "CS" "BT" bears S62°19'W, 40.15 feet.

The Northeast corner of wood frame house, bears N50°33'W.

Corner lies in middle of road, about 20 feet West of private drive, c. South, to residence 975 Anderson Creek Road.

October 8, 1984
R. Frost
E. McGinty

Edward McGinty
County Surveyor

V = 16°
P. -111

SEE NEXT PAGE FOR FIFTH RE-ESTABLISHMENT


FIFTH RE-ESTABLISHMENT

DLC67NW

GCDB 867110

Northwest corner to DLC No. 67, located in Section 34, Township 38 South, Range 1 West, W.M.

Found the center punched brass cap recorded on the Fourth Re-establishment, dated 1984, in concrete, 8 inches deep in monument case.



References reported in 1984 found:

- The Westerly branch, 22-inch diameter of a triple Black Oak, with healed blazes, bears $N65^{\circ}05'39''E$, 60.2 feet. Record $N65^{\circ}06'E$ to center of said branch at upper blaze.
- Gas pipe $\frac{1}{2}$ -inch diameter 2 ins. deep and located at the northerly end of a north-south bearing barbed wire fence in between residences 999 and 981 Anderson Creek Road. Bears $S0^{\circ}12'31''E$, 20.05 feet. Record $S0^{\circ}12'W$, 19.95 feet.
- Rebar $\frac{5}{8}$ ins. diameter rebar 4 inches deep, bears $S51^{\circ}40'47''E$, 41.49 feet. Record $S50^{\circ}33'E$, 40.36 feet. Located near the Southerly right of way of Anderson Creek Road and 4 feet northerly of a twin branched 12 ins. diameter oak.
- The Northeast corner of wood frame house, bears $N50^{\circ}50'45''W$, 159.61 feet. Record $N50^{\circ}33'W$ No record distance.

Corner lies in middle of road, about 20 feet West of private drive, c. South, to residence 975 Anderson Creek Road.

Basis of Bearing: NAD 83 2011 Epoch (2010) OCRS GP/ASH zone per OAR 734-005-0015

August 7, 2017
J. Hall

Scott Fein
Jackson County Surveyor