

FIRST RE-ESTABLISHMENT

DLC68SW

GCDB 868120

Southwest corner of Donation Land Claim No. 68, located in Section 26, Township 38 South, Range 1 West, W.M.

Utilizing data gathered during the execution of Survey No. 11287:

- Set a 1x36-inch Galvanized iron pipe over the top of a found 7/8 inches square head bolt, 18 inches long and 2 inches deep.

In the top of said pipe, set in concrete, a 2½-inch diameter brass cap marked:

T38S R1W
DLC
SW 68
CS
1988

A possible stump depression bears N6°41'E, 45.52 feet to estimated center. Record: N10°E, 45.54 feet.

Scribe new trees CS-BT and measure to center of trees at lower blaze:

- White Oak, 13-inch diameter, bears S51°43'25"W, 66.53 feet.
- White Oak, 11-inch diameter, bears N36°34'19"W, 39.38 feet.

An old wooden corner post to partially down fences bearing North, South and East bears S43°30'W, 24.5 feet.

Corner lies on an extremely brushy west slope, 18 feet East and 13.5 feet North of an east-west fence.

August 23, 1988
D. Edwards, Tech.
T. Newcomb, Tech.

Edward McGinty
County Surveyor

See Job File 88-57

P. -321