

**FIRST RE-ESTABLISHMENT**

**DLC70SW**

**GCDB 870123**

Southwest corner to DLC #70, Township 38 South, Range 1 West.

Set an Oliver plow share point up for corner.

From which:

- The stump of the original BT, a Black Oak bears  $S02^{\circ}W$ , 52.8 feet;
- Scribe a 4" white oak which bears  $N72^{\circ}30'W$ , 59.0 feet;
- The center of a concrete foundation block 2 feet square at the SW corner of a barn bears  $N04^{\circ}E$ , 88.0 feet.

June 9, 1925  
C. Z. Boyden,  
Deputy County Surveyor

H. Wheeler, Chainman

**SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT**

## SECOND RE-ESTABLISHMENT

DLC70SW

GCDB 870123

Southwest corner of DLC No. 70, Township 38 South, Range 1 West, W.M.

Found the Oliver plow share monument as set for corner by Deputy County Surveyor C. Z. Boyden on June 9, 1925.

No evidence could be found of either tree described in said First re-establishment. The barn as mentioned in said re-establishment has been altered and rebuilt, but it is evident that the reported tie was meant to refer to the Southeast corner of the barn, rather than the Southwest barn corner.

Replaced said plow share corner monument with a 1" x 36" galvanized iron pipe, with bronze cap stamped:

T38S R1W  
S.W. | Cor.  
└───┘  
c.s.  
DLC 70  
1965

Set 32" in the ground for corner.

From which:

- Scribed a 36" Black Oak, "CS-BT" which bears  $S1^{\circ}W$  105.9 feet to the face of the lower blaze.
- Scribed a 16" Yellow Pine, "CS-BT" which bears  $N79\frac{1}{4}^{\circ}W$  212.2 feet to the face of the upper blaze.
- The southeast corner of the existing barn bears  $N4\frac{3}{4}^{\circ}E$  70.9 feet.

January 8, 1965  
F. A. Roberts,  
Gary Kaiser  
Lloyd W. Miller, Present

Approved by:  
Mark Boyden,  
County Surveyor

SEE NEXT PAGE FOR THIRD RE-ESTABLISHMENT

### THIRD RE-ESTABLISHMENT

DLC70SW

GCDB 870123

Southwest corner to DLC No. 70, located in Section 23, Township 38 South, Range 1 West, W.M.

Found 16 inches deep, the brass cap, described on Second re-establishment in 1965.

Bearing trees marked in 1965 found:

- Black Oak, 39-inch diameter, with partially exposed upper face, bears  $S0^{\circ}46'W$  106.53 feet to said face. Record:  $S1^{\circ}W$  105.9 feet.
- Ponderosa Pine, 21-inch diameter, with healed blazes, bears Record:  $N79^{\circ}15'W$  212.2 feet to estimated upper face. Re-measured 212.89 feet to center of tree at upper blaze.
- The barn reported in 1965 is now gone.

Set new references;  $\frac{5}{8}$  x 30-inch rebars flush with yellow plastic caps marked "Jackson C.S." bears:

- $N58^{\circ}25'E$  58.11 feet, located  $1\frac{1}{2}$  feet South of board fence.
- $S58^{\circ}25'W$  29.16 feet, located 1 foot East of board fence.

The (brass cap) S.E. corner of DLC #68, bears  $N0^{\circ}12'W$  375.03 feet.

Corner lies about 9 feet  $N45^{\circ}W$  of the center in curve of gravel road.

October 29, 1984  
E. McGinty  
R. Frost

Edward McGinty  
County Surveyor

P. 115-116A