

FIRST RE-ESTABLISHMENT

DLC81NE

GCDB 881100

Northeast corner DLC #81, Township 38 South, Range 1 West.

Found a 1¼" x 1" x ? "U" bar with ¾" pin driven alongside located 9" below the road surface, which "U" bar has been the recognized corner for over 50 years according to the testimony of Lester Carr, an old time resident. No original corner evidence could be found.

From said "U" bar:

- The center of a 15" English Walnut tree bears N49½°E, 52.3 feet;
- The center of a 6" English Walnut tree bears S25½°E, 89.3 feet;
- Chiseled a cross on a concrete wall at the Northwest corner of a cattle guard which bears N77½°E, 11.64 feet.

December 19, 1956
Mark E. Boyden
K. D. Weaver

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

DLC81NE

GCDB 881100

Northeast corner of DLC No. 81, Township 38 South, Range 1 West, W.M.

Found the "U" bar corner monument and reference trees as reported on the First Re-establishment dated December 19, 1956.

The cattle guard reference has been destroyed by recent road construction.

Replaced said "U" bar with a 1" x 36" galvanized iron pipe set 6" below the road surface with the 2½" bronze cap stamped:

T38S, R1W
NE | DLC
Cor. | 81
c.s.
1966

From said pipe corner:

- Set a 5/8" x 30" iron pin which bears N89°18'20"W, 30.00 feet.
- Found a 5/8" iron pin set on Recorded Survey No. 2931 which bears S89°36'20"E, 30.00 feet.
- The Southeast corner of the concrete foundation of a one-story wood frame residence bears N58°32'W, 75.1 feet.

June 3, 1966
F. A. Roberts
B. Grant

Approved by:
M. E. Boyden,
County Surveyor

SEE NEXT PAGE FOR THIRD RE-ESTABLISHMENT

THIRD RE-ESTABLISHMENT

DLC81NE

GCDB 881100

Northeast corner to DLC No. 81 located in Section 11, Township 38 South, Range 1 West, W.M.

Found in the middle of and 12 inches below the asphalt surface of Payne Road, the center-punched brass cap described on Second re-establishment in 1966.

References recorded in 1966 found:

- Iron pin, found 12 inches deep bears S89°36'E, 29.85 feet. Record: 30.00 feet.
- The Southeast corner of concrete foundation of wood frame house bears Record: N58°32'W, 75.1 feet.

Marked a new reference:

- Chiseled cross atop the South end of a 12-inch diameter concrete culvert, under the driveway to residence 3100 Payne Road, bears N86°11'W, 21.70 feet.
- The brass cap northeast corner of DLC No. 82 bears N89°18'W.

July 9, 1984
R. Frost
E. McGinty

Edward McGinty
County Surveyor

V = 18½°
P. -81

NOTE: Jackson County Dept. of Public Works set brass cap 7/19/84 marked:

T38S R1W
DLC

NE
81
C.S.

1984