

FIRST RE-ESTABLISHMENT

DLC82NW

GCDB 842100

North Northeast corner of DLC #42, Township 38 South, Range 1 West, W.M. (also NW DLC #82)

Located this corner, from evidence of old settlers, at the junction of two fences. All evidence of the original corner is gone, as the original monument was a mound of earth and a pint of charcoal. All agreed that the original corner was at the point where the present fences join.

From this point the measurement to a fence said to be on the North and South half section line of Section 10 checks.

- Set a ½" gas pipe to mark the corner.
- No trees near for reference.

June 1913
A. T. Brown,
Deputy County Surveyor

M. B. Kellogg, Chainman
C.D. Runyon, Chainman

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

DLC82NW

GCDB 842100

North-Northeast corner Donation Land Claim No. 42, Township 38 South, Range 1 West. (Also being the NW corner to DLC #82)

Found the ½" pipe for corner and replaced it with a 1"x36" galvanized iron pipe set 36" in the ground with a 2½" bronze cap stamped:

T38S, R1W
DLC NE Cor.
42
C.S.
1967

From which:

- A 12" White Oak scribed CS-BT, bears North 79°42' West, 370.0 feet to the lower blaze:
- A 5/8"x30" iron pin bears South 0°13' West, 30.0 feet;
- A 5/8"x30" iron pin bears South 89°53' East, 30.0 feet.

February 23, 1967
F. A. Roberts
G. Nygren

Approved by:
L. D. Pinkham
Deputy County Surveyor

SEE CORNER REPORT CARD - dated May 17, 1988

SEE NEXT PAGE FOR THIRD RE-ESTABLISHMENT

THIRD RE-ESTABLISHMENT

DLC82NW

GCDB 842100

North-Northeast corner Donation Land Claim No. 42, Township 38 South, Range 1 West. (Also being the NW corner to DLC #82.)

Found 2½ ins. diam. brass cap on a 1 ins. diam. GIP marked:

T38S R1W
DLC
NE COR
42
C.S.
1967

Corner and references lie in dense patch of blackberries on the northwest corner of a pasture. Impractical to set new references or locate references from the second re-establishment.

Therefore, through static GPS observation utilizing the Jackson County Surveyor's CORS station (JUSTICE 2) and ODOT ORGN CORS stations (Ashland and Central Point) with NAD 83 (1991 HARN) positions as determined by the Jackson County Surveyor, determine a NAD 83, Oregon South Zone 3602 position and a NAVD 88 orthometric height for this DLC corner. Position was calculated utilizing Geoid 03 and GRS 80 ellipsoid, with redundant GPS observations processed in Trimble Geomatics Office V1.62 and verified with a minimally constrained least squares adjustment.

NAD 83 (1991)
N 233936.224
E 4297475.274

NAVD 88
Elevation: 1550.41

January 28, 2010
S.Fein
S. Beecher

Jackson County Surveyor
Kerry K. Bradshaw

Series II Book I
P. -3