

FIRST RE-ESTABLISHMENT

DLC82SW

GCDB 882100

Southwest corner of DLC #82 on the East line of Claim #42, Township 38 South, Range 1 West, W.M.

Found the original witness tree in claim #42, a 14" White Oak which bears West 3 links from the corner.

Set ½" gas pipe for corner.

- At the proper bearings and distances found remains of the two other original trees.

Set two new trees as follows:

- A 24" Black Oak scribed C 82 T38S R1W CS on the upper and BT on the lower blaze, bears N35½°E, 132.6 feet.
- An 18" Black Oak scribed C 82 S10 T38S R1W CS on the upper and BT on the lower blaze, bears S56¼°E, 99.9 feet.

April 2, 1914
A. T. Brown,
Deputy County Surveyor

H. Ling, Chainman

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

DLC82SW

GCDB 882100

Southwest corner of DLC #82, Township 38 South, Range 1 West, W.M.

Found the ½" iron pipe, the stump of the Black Oak BT to the NE with scribing visible, and the Black Oak BT to the SE in poor condition with scribing visible. All of which was reported by County Surveyor Brown in April 1914, in the First Re-establishment.

Also found the original White Oak BT to the West and the stump hole of the original BT to the NE. All of which evidence was reported by Brown and agrees with the ½" pipe for the location of the corner.

Drove a 1½" x 24" galvanized iron pipe around said ½" iron pipe for corner.

From which:

- A 12" White Oak scribed CS-BT bears N31¾°E, 83.8 feet.
- A 10" White Oak scribed CS-BT bears S17½°E, 47.3 feet.
- A 6" White Oak scribed CS-BT bears S15½°W, 26.6 feet.

August 18, 1950

C. Z. Boyden

L. D. Pinkham

M. E. Boyden

SEE NEXT PAGE FOR THIRD RE-ESTABLISHMENT

THIRD RE-ESTABLISHMENT

DLC82SW

GCDB 882100

Southwest corner to Donation Land Claim No. 82, located in Section 10, Township 38 South, Range 1 West, W.M.

Found an unrecorded 3-inch diameter brass cap marked:

T38S	R1W
DLC	SW
Cor.	82
C.S.	
1971	

Set flush in a large cement concretion.

First Re-establishment references, page 3, dated 1914, found:

- Black Oak, 20-inch diameter with healed blazes bears Record: S56¼°E, 99.9 feet to center.

Second Re-establishment references, page 19, dated 1950, found:

- White Oak, 17-inch diameter bears N32½°E, 83.8 feet to estimated upper face. Re-measure 84.7 feet to center of tree at base. Record bearing; N31¾°E.
- White Oak, 14-inch diameter bears Record: S17½°E, 47.3 feet to estimated upper face. Re-measure 47.9 feet to center of tree at base.
- White Oak, 14-inch diameter bears Record: S15½°W, 26.6 feet to estimated upper face. Re-measure 27.0 feet to center of tree at base.

Set 5/8 x 24-inch rebars with yellow plastic caps marked "Jackson C.S." 1 foot East of North-South fence line:

- S02¼°W, 8.90 feet.
- N03°W, 18.62 feet.

Corner lays 1 foot East of North-South fence line on North slope approximately 250 feet south of irrigation canal.

May 24, 1988
S. Beecher, Tech.
R. Frost, Tech.

Edward McGinty
County Surveyor

V = 17°
P. -205