

FIRST RE-ESTABLISHMENT

DLC83ENE

GCDB 884130

Southeast corner of DLC #84, also the East Northeast corner of DLC #83, Township 38 South, Range 1 West, W.M.

All the witness trees destroyed.

Found pile of rocks in the fence line which men on the ground said was the accepted corner. This point checks in measurement and bearings from the Southwest corner of Claim #84, the Southeast corner of claim #83, and the $\frac{1}{4}$ Section corner between sections 2 and 3.

Drove an iron bar for corner in the center of the above mentioned rock pile. No trees near for reference.

October 15, 1913
A. T. Brown,
Deputy County Surveyor

L. Wilson, Chainman
F. Reed, Chainman

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

DLC83ENE

GCDB 884130

Southeast corner of DLC #84, Township 38 South, Range 1 West, W.M. (Also the East Northeast corner DLC #83)

Found the iron bar set in a mound of stone as set by County Surveyor A. T. Brown, October 1913.

Set a 1½" x 36" galvanized iron pipe 36" in the ground for corner at the exact location of the said iron bar.

From which:

- The corner of the concrete foundation at the Southwest corner of a two-story wood frame residence bears S26½°E, 137.8 feet.
- The center of a 6" locust tree bears South 38.7 feet.
- Scribe a 22" White Oak CS-BT on one blaze which bears N77¾°E, 336.9 feet.
- The ½" iron pipe at the ¼ section corner common to Sections 2 and 3 bears N85¼°E, 881.6 feet.
- At a point N36°50'E, 684.0 feet, found the stump of the original Northeast BT with scribe intact for the East Northeast corner DLC #84.

February 3, 1954

C. Z. Boyden

L. D. Pinkham

M. E. Boyden

SEE NEXT PAGE FOR THIRD RE-ESTABLISHMENT

THIRD RE-ESTABLISHMENT

DLC83ENE

GCDB 884130

Southeast corner to Donation Land Claim No. 84, identical with the East Northeast corner of Donation Land Claim No. 83, located in Section 3, Township 38 South, Range 1 West, W.M.

Found 3 inches deep, brass cap set in concrete, containing stamped marks including:

DLC | SE
Cor. | 84
C.S.
1971

References recorded on Second Re-establishment in 1954 found:

- Locust tree, 9-inch diameter, now a snag, bears Record: South, 38.7 feet.
- The Southwest corner of two-story wood frame house bears Record: S26½°E, 137.8 feet.

To perpetuate this location, set new references:

- Rebar, 5/8 x 24 inches, with yellow plastic cap marked: JACKSON County C.S., set flush, 0.8 feet South of fence line, bears S89°57'E, 20.86 feet.
- Chiseled cross atop the Northeast corner of 3 x 3½ feet concrete irrigation box, bears S3°55'W, 42.43 feet.
- The staff of beacon light atop the South end of the Rogue Valley Manor bears N66°16'W.

Corner lies 11.4 feet, S76°E of Power Pole No. 9/24, 18 feet North of the middle of gravel road c. East-West and 0.5 feet South of East-West fence line.

July 16, 1984
R. Frost
E. McGinty

Edward McGinty
County Surveyor

V = 18°
P. - 88