

## FIRST RE-ESTABLISHMENT

GCDB 140500

Quarter corner common to Sections 7 and 18, Township 39 South, Range 3 East, W.M.

Set a 1" x 36" galvanized iron pipe 34" in the ground with a 2½" bronze cap stamped:

T39S R3E  
7  
¼S — Cor.  
18  
C.S.  
1971

For corner.

From which:

- The original bearing tree, now a 48" Fir stump, bears S7°E, 4.1 feet to center of the stump. Record: 50" Fir, S8°E, 2.0 feet.
- The original bearing tree, now a down 12" White Fir snag scribed "¼S - BT", bears N82°E, 5.0 feet to center of the stump. Record: 20" Fir, N85°E, 4.6 feet.

Marked the following new trees:

- A 12" White Fir scribed "CS-BT" bears N40¾°E, 14.8 feet to face of the lower blaze.
- A 11" White Fir scribed "CS-BT" bears S48°E, 24.6 feet to face of the lower blaze.

August 20, 1971  
Otis Blankenship  
Otis Blankenship III  
Mrs. G. Turnbaugh, Present

Approved by  
M. E. Boyden,  
County Surveyor

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

## SECOND RE-ESTABLISHMENT

GCDB 140500

Quarter corner common to Sections 7 and 18, Township 39 South, Range 3 East, W.M.

Found at the corner position, the 1-inch diameter galvanized iron with a 2½-inch diameter brass cap, set on First Re-establishment in 1971, exposed 6 inches and marked:

T39S R3E  
7  
¼S — Cor.  
18  
C.S.  
1971

Bearing trees recorded by E. T. T. Fisher in 1858, found and measured to center of deteriorated stump remains:

- Fir bears S 7° E, 4.1 feet, Record: 1.98 feet to face.
- Fir bears S 85° E, 5.0 feet. Record: 4.62 feet to face.

Bearing tree recorded on said First Re-establishment, found and measured to center of tree at lower blaze:

- White Fir, now 14-inch diameter with healed double blazes bears S 48° E, 25.0 feet. Record: 24.6 feet to face of lower blaze.

Marked new bearing trees "CS" "BT" and took measurements to center of trees at lower blaze:

- White Fir 8-inch diameter bears N 51½° E, 13.1 feet.
- White Fir 9-inch diameter bears S 31¾° W, 26.6 feet.
- White Fir 9-inch diameter bears N 37° W, 23.6 feet.

Corner lies approximately 200 feet west of graveled road on steep westerly slope.

May 24, 2005  
H. Durkee

Roger R. Roberts  
Jackson County Surveyor

P. - 64  
V. - 19°