

FIRST RE-ESTABLISHMENT

GCDB 200140

One-quarter corner common to Sections 31 and 32, Township 39 South, Range 3 East, W.M.
 $V = 16\frac{3}{4}^\circ$

Found 5/8-inch diameter rebar projecting 3 inches established on BLM Administrative Survey No. 16 in 1978, of Jackson County Surveyors Records.

I drive over said rebar, a 1 x 36-inch Galvanized iron pipe projecting 6 inches with 2½-inch bronze disc marked:

JACKSON COUNTY 1979
31 | 32

From which I found the following original bearing trees established by E.T.T. Fisher in 1858:

- Black Oak, 25-inch diameter, scribed "¼S" bears $N2\frac{1}{2}^\circ W$, 176.12 feet. Record: $N2\frac{1}{2}^\circ W$, 174.9 feet.
- Black Oak, 15-inch diameter, rotted out face, bears $N61^\circ E$, 192.31 feet. Record: $N62^\circ E$, 191.4 feet.

I mark the following trees "CS BT" and took measurements to center of trees at lower blaze:

- Ponderosa Pine, 10-inch diameter bears $S79\frac{1}{4}^\circ W$, 151.10 feet.
- Douglas Fir, 10-inch diameter bears $N61^\circ E$, 174.37 feet.

Corner lies 5 feet North of metal fence post and $N7^\circ E$, 78.11 feet from Northsouth-Eastwest fence lines corner post.

Location tag is alongside road.

Corner lies about 1000 feet North.

June 5, 1979
B. Malotte
J. Gallegos

Approved by: Edward McGinty
County Surveyor