

FIRST RE-ESTABLISHMENT

GCDB 200300

Section corner common to Sections 19, 20, 29 and 30, Township 39 South, Range 3 East, W.M.

Found original BT to Southwest, also stump of BT to Northeast. Set a 3" x 3" x 36" stake for corner.

From which:

- A 10" White Fir scribed CS-BT bears N36°45'E, 4.2 feet.
- A 16" Red Fir scribed CS-BT bears S57°30'E, 20.6 feet.
- A 12" Red Fir scribed CS-BT bears S36°30'W, 42.5 feet.

June 10, 1929
Boyden,
Deputy County Surveyor

McKay, and Pettegrew, Chainmen

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 200300

Section corner common to Sections 19, 20, 29 and 30, Township 39 South, Range 3 East, W.M.

Found at the corner position, exposed 3 inches and in a mound of stones, the 2-inch diameter galvanized iron pipe with a 3½-inch diameter brass cap set by the BLM in 1967, marked:

T39S	R3E
S19	S20
S30	S29
1967	

A ¾-inch diameter galvanized iron pipe, exposed 6 inches, found against northwesterly edge of monument.

Single remaining bearing tree recorded by E. T. T. Fisher in 1858, a fir, now 28-inch diameter with healed blazes bears S 29° W, 81.2 feet to center at lower blaze. Record: S 27° W, 81.84 feet.

Bearing trees recorded on First Re-establishment in 1930, found and measured to center of trees at lower blaze;

- White Fir snag, now 20-inch diameter with opened blazes revealing scribe marks "CS BT" bears Record: N 36° E, 4.6 feet.
- Fir, now 33-inch diameter with healed blazes bears Record: S 37° W, 42.5 feet.

Bearing trees recorded by the BLM in 1967 found and measured to center of trees at base:

- Fir, dead and down bears S 65° E, 21.8 feet to center of stump. Record: 21.5 feet.
- Fir, now 22-inch diameter with healed single blaze bears Record: N 71° W, 27.4 feet.

Marked new bearing tree "CS" "BT" and take measurement to center of tree at lower blaze:

- Douglas Fir, 14-inch diameter, bears S 36° E, 74.2 feet.

Corner lies approximately 300 feet east of spur Road and approximately 70 feet east of Pacific Crest Trail.

June 29, 2005
H. Durkee

Roger R. Roberts
Jackson County Surveyor

P. - 90
V. - 15°40'