

**FIRST RE-ESTABLISHMENT**

**GCDB 200440**

Quarter corner common to Sections 17 and 18, Township 39 South, Range 3 East, W.M.

Set a 1" x 36" galvanized iron pipe 28" in the ground with 2½" bronze cap stamped:

T39S R3E  
¼ 18 | 17 Cor.  
C.S.  
1971

For corner.

From which:

- The original bearing tree, now a 39" Fir with scribe "S" visible, bears N81°W, 22.4 feet to face of the upper blaze.
- A rotted Fir stump at location of the original bearing tree bears N51°E, 27.4 feet to center of the stump.

Marked the following new trees:

- A 15" White Fir scribed CS-BT bears S42°E, 20.4 feet to face of the lower blaze.
- A 15" White Fir scribed CS-BT bears S73°W, 33.3 feet to face of the lower blaze.

August 20, 1971  
Otis Blankenship  
Otis Blankenship III  
Mrs. G. Turnbaugh, Present

Approved by:  
M. E. Boyden,  
County Surveyor

**SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT**

## SECOND RE-ESTABLISHMENT

GCDB 200440

Quarter corner common to Sections 17 and 18, Township 39 South, Range 3 East, W.M.

Found at the corner position, exposed 6 inches, the 1-inch diameter galvanized iron pipe with a 2½-inch diameter brass cap set on First Re-establishment in 1971, marked:

T39S R3E  
|  
¼ 18 | 17 Cor.  
|  
C.S.  
1971

Single remaining bearing tree recorded by E. T. T. Fisher in 1858,

- A large fir dead and down, bears N81° W, 23.0 feet to center of stump hole, Record: 22.4 feet to face.

Bearing trees recorded on said First Re-establishment found and measured to center of trees at lower blaze:

- White Fir snag, now 15-inch diameter with exposed faces and visible scribe marks "CS" "BT" bears S42° E, 21.0 feet. Record: 20.4 feet to face.
- White Fir dead and down, bears S72° W, 33.7 feet to center of stump hole. Record: S73° W, 33.3 feet to face.

Marked new bearing trees "CS" "BT" and took measurements to center of trees at lower blaze:

- White Fir 7-inch diameter bears N77° E, 13.7 feet.
- White Fir 12-inch diameter bears S18½° W, 84.7 feet.
- White Fir 6-inch diameter bears N 62°W, 40.0 feet.

Corner lies approximately 75 feet west of blocked spur road.

May 24, 2005

H. Durkee

Roger R. Roberts  
Jackson County Surveyor

P. - 65

V. - 14°45'