

FIRST RE-ESTABLISHMENT

GCDB 200540

Quarter corner common to Sections 7 and 8, Township 39 South, Range 3 East, W.M.

Set a 1" galvanized iron pipe, exposed 6", with a 2½" bronze cap stamped:

T39S R3E
¼ 7 | 8 Cor.
C.S.
1971

For corner.

From which:

- The original bearing tree, now a 30" Cedar snag with "BT" scribe visible, bears N80¾°W, 17.2 feet to the lower face. Record: 24" Cedar N80°W, 17.2 feet.
- The center of a stump hole bears S15¾°E, 6.7 feet. Record: 18" Fir, S15°E, 5.9 feet.

Marked new trees as follows:

- A 16" White Fir, scribed CS-BT bears N19°W, 13.8 feet to face of the lower blaze.
- An 18" White Fir, scribed CS-BT bears N36¾°E, 3.4 feet to face of the lower blaze.

August 26, 1971
Otis Blankenship
Dan Phillips

Approved by:
M. E. Boyden,
County Surveyor


SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 200540

Quarter corner common to Sections 7 and 8, Township 39 South, Range 3 East, W.M.

Found at the corner position, exposed 6 inches and in a mound of stones, the 1-inch diameter galvanized iron pipe with a 2½-inch diameter brass cap set on First Re-establishment in 1971, marked:



Single remaining bearing tree recorded by E. T. T. Fisher in 1858, found and measured to center of tree at lower blaze:

- Cedar, now 30-inch diameter with opened weathered upper blaze bears N 80° W, 18.5 feet. Record: 17.2 feet to face.

Bearing trees recorded on said First Re-establishment, found with double healed blazes, and measured to center of trees at lower blaze:

- White Fir, now 21-inch diameter bears N 19° W, 14.4 feet. Record: 13.8 feet to face.
- White Fir, now 22-inch diameter bears N 36¾° E, 4.3 feet. Record: 3.4 feet to face.

Marked new bearing trees "CS" "BT" and took measurements to center of trees at lower blaze:

- White Fir 10-inch diameter bears S 79° E, 7.0 feet.
- White Fir 13-inch diameter bears S 78¾° W, 61.6 feet.

Corner lies on gentle southerly slope, near top of ridge and approximately 600 feet west of old spur road.

June 6, 2005
H. Durkee

Roger R. Roberts
Jackson County Surveyor

P. - 74
V. - 17°50'