

FIRST RE-ESTABLISHMENT

GCDB 240600

Quarter corner common to Sections 5 and 8, Township 39 South, Range 3 East, W.M.

Set a 1" x 36" galvanized iron pipe, 32" in the ground with 2½" bronze cap stamped:

T39S R3E
5
¼S — Cor.
8
C.S.
1972

For corner.

From which:

- The original bearing tree, now a 30" Fir with lower blaze partially open, bears N28°E, 7.3 feet to face of the lower blaze. Record: 20" Fir, N28°E, 7.26 feet.
- The original bearing tree, now a 24" Fir snag with "BT" scribe visible, bears S15½°W, 12.5 feet to face of the lower blaze. Record: 22° Fir S12°W, 12.54 feet.

Marked a new tree as follows:

- A 16" Fir, scribed CS-BT bears S13¾°E, 50.2 feet to face of the lower blaze.

June 5, 1972
Lloyd Shreeve
Ray Webber

Approved by: Gary D. Kaiser
Deputy County Surveyor

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 240600

Quarter corner common to Sections 5 and 8, Township 39 South, Range 3 East, W.M.

Found at the corner position, flush and in a ring of stones, the 2½-inch diameter brass cap set on First Re-establishment in 1972, marked:

T39S R3E
5
¼S — Cor.
8
C.S.
1972

Bearing trees recorded by E. T. T. Fisher in 1858, found and measured to center of trees at lower blaze:

- Fir snag, now 30-inch diameter with healed blazes bears N 28° E, 7.7 feet. Record: 7.3 feet to face.
- Rotted mound of fir remains bears S15½° W, approximately 13.0 feet to center of mound. Record: 12.5 feet to face.

Bearing tree recorded on said First Re-establishment, ins 1972, found and measured to center of tree at lower blaze:

- Fir, now 20-inch diameter with healed blazes bears S 13¾° E, 50.7 feet. Record: 50.2 feet to face.

Bearing tree marked by the BLM in 1993 found and measured to center of tree at base:

- White Fir, now 32-inch diameter with partially healed blaze revealing scribe marks "¼ S5 BT" bears N38½° W, 71.7 feet. Record: 71.28 feet (Record per BLM tag on tree dated 1993).

Marked new bearing trees "CS" "BT" and took measurements to center of trees at lower blaze:

- White Fir 9-inch diameter bears S62° W, 30.3 feet.
- White Fir 11-inch diameter bears S70° E, 32.7 feet.

Corner lies approximately 1000 feet east of graveled road at top of ridge.

June 2, 2005
H. Durkee

Roger R. Roberts
Jackson County Surveyor

P. - 73
V. - 16°50'