

## FIRST RE-ESTABLISHMENT

GCDB 300340

Quarter corner common to Sections 20 and 21, Township 39 South, Range 3 East, W.M.  $V = 20^\circ$

From the following original evidence, at the location described below, I set a 1 x 36-inch Galvanized iron pipe 34 inches in the ground with a 2½-inch bronze disc marked:

T39S R3E  
¼S  
20 | 21  
C.S.  
1973

From which:

- An original BT., now a hollow, sawed Fir stump, 30-inch diameter, containing reversed impression of partial scribed "BT", bears record,  $S7^\circ W$ , 122.10 feet.
- The stump hole of original NE BT with Fir fragments alongside, containing partial scribed "¼S", bears record,  $N89^\circ E$ , 13.86 feet.

I mounded stone around corner, marked the following trees CS BT and took measurements to center of tree at lower blaze:

- A Douglas Fir, 13-inch diameter, bears  $S31^\circ E$ , 28.0 feet.
- A Douglas Fir, 14-inch diameter, bears  $S89^\circ W$ , 29.8 feet.

Corner lies on East edge of rock outcropping, approximately 800 feet East of location marker on fence post alongside road.

October 25, 1973  
B. Malotte  
R. Frost

Approved by: Edward McGinty  
County Surveyor