

FIRST RE-ESTABLISHMENT

GCDB 300440

Quarter Corner common to Sections 16 and 17, Township 39 South, Range 3 East, W.M.

Found the 5/8" rebar in mound of rock exposed 12" with aluminum cap stamped:

WEYERHAEUSER
1/4
17 | 16
1969
ORLS 686

As reported on Recorded Survey No. 4191.

From which:

- The original bearing tree (now a 48" Fir with top gone and bark scribed "1/4S - BT") bears N10°W, 33.3 feet to the lower scribe. Record: 30" Fir, N10°W, 35.6 feet.
- The original bearing tree, (now a 22" Fir snag with both faces open and rotted and with some scribe marks visible) bears S78 3/4°E, 96.8 feet to the face of the upper blaze. Record: 18" Fir, S83°E, 99.0 feet.

Marked the following new trees:

- A 9" White Fir, scribed CS-BT bears N29°E, 69.2 feet to the face of the lower blaze.
- A 14" White Fir, scribed CS-BT bears N76 1/2°W, 116.8 feet to the face of the lower blaze.

August 19, 1971
Otis Blankenship
Lloyd Shreeve

Approved by:
M. E. Boyden,
County Surveyor

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 300440

Quarter corner common to Sections 16 and 17, Township 39 South, Range 3 East, W.M.

Found, at the corner, projecting 12 inches, the 5/8-inch diameter rebar with "Weyerhaeuser" aluminum cap affixed to the top, recorded as found on First Re-establishment in 1971.

Removed said aluminum cap and set over top of said 5/8-inch diameter rebar, a 1 x 36-inch Galvanized iron pipe, projecting 12 inches, in a mound of stones, with a 2½-inch diameter brass cap marked:

T39S R3E
¼S
17 | 16
C.S.
1991

Original bearing trees, recorded as marked by Sewall Truax in 1859, found:

- Fir snag, now 48-inch diameter with chain saw and axe damage to bark scribing, bears Record: N10°W, 35.6 feet to center of tree at base.
- Fir snag, now 22-inch diameter, with open and rotted blazes, bears S79°E, 97.0 feet to face of upper blaze. Record: S83°E, 99.0 feet.

Bearing trees recorded as marked on said First Re-establishment found:

- White Fir, now 14-inch diameter, with double healed blazes, bears N29°E, 69.8 feet to center of tree at lower blaze. Record: 69.2 feet to face of lower blaze.
- White Fir, now 20-inch diameter, with double healed blazes, bears N76½°W, 117.2 feet to center of tree at lower blaze. Record: 116.8 feet to face of lower blaze.

Set new reference: Top of Mt. Shasta, bears S14¼°E.

Corner lies about 80 feet Southerly of the top of Ridge; Course S80°E.

July 10, 1991
H. Durkee, Tech.
T. Newcomb, Tech.

Verlyn Thomas
County Surveyor

V = 18°
P.-50