

**FIRST RE-ESTABLISHMENT**

**GCDB 300500**

Section corner common to Sections 8, 9, 16 and 17, Township 39 South, Range 3 East, W.M.

Found a 5/8" iron pin exposed 14" in a mound of rock, with a 1½" aluminum cap stamped:

WEYERHAEUSER	
T39S	R3E
8	9
-----	
17	16
1969	
ORLS 686	

As reported on Recorded Survey No. 4191.

From which:

- The original bearing tree, now a 31" Fir snag with healed blazes, bears S58¼°W, 174.6 feet to the center. Record: 12" Fir, S57°W, 176.9 feet.
- The original bearing tree, now a down Fir snag with scribe visible, the center of a stump hole, bears North 213.7 feet. Record: 24" Fir, N4°W, 214.5 feet.

Marked the following new trees:

- An 18" Cedar scribed CS-BT bears N10¾°W, 252.9 feet to face of the lower blaze.
- A 14" Fir scribed CS-BT bears S24¼°E, 173.2 feet to face of the lower blaze.
- A 17" Fir, scribed CS-BT bears S67¼°W, 156.8 feet to face of the lower blaze.
- A 16" Fir, scribed CS-BT bears N83½°E, 104.8 feet to face of the lower blaze.

August 25, 1971  
Dan Phillips  
Otis Blankenship

Approved by:  
M. E. Boyden,  
County Surveyor

**SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT**

## SECOND RE-ESTABLISHMENT

GCDB 300500

Corner common to Sections 8, 9, 16 and 17 in Township 39 South, Range 3 East, W.M.

Found at the corner, projecting 14 inches, the 5/8-inch diameter iron pin with 1½-inch diameter aluminum cap, recorded as found on First Re-establishment, dated August 25, 1971.

Replaced said monument with and lay alongside of, a 1x36-inch Galvanized iron pipe, projecting 14 inches, in a mound of stones, with a 2½-inch diameter brass cap marked:

T39S	R3E
8	9
17	16
CS	
1991	

Single remaining original bearing tree recorded by Sewall Truax in 1859, found:

- Fir snag, 31-inch diameter with healed blazes bears S58¼°W, 174.6 feet. Record: S57°W, 176.9 feet.

Bearing trees recorded as marked on First Re-establishment, found and measured to center of tree at lower blaze:

- White Fir, now 22-inch diameter, with partially healed blazes, bears S67¼°W, 157.7 feet. Record: 156.8 feet to lower blaze.
- White Fir, now 19-inch diameter, with partially healed blazes, bears S23¾°E, 173.5 feet. Record: S24¼°E, 173.2 feet to lower blaze.
- White Fir, now 20-inch diameter, with partially healed blazes, in northeast quadrant now down. Accurate measurement not possible.
- Cedar, now 22-inch diameter with healed blazes, bears N10¾°W, 255.2 feet. Record: 252.9 feet to lower blaze.

Marked new bearing tree "CS" "BT":

- White Oak, 5-inch diameter, bears N60½°E, 74.9 feet, to center of tree at lower blaze.

Corner lies on barren westerly slope, about 120 feet west of dirt road.

February 7, 1991  
H. Durkee, Tech.  
T. Newcomb, Tech.

Verlyn Thomas  
County Surveyor

V = 18½°  
P.-2