

**FIRST RE-ESTABLISHMENT**

**GCDB 340500**

Quarter corner common to Sections 9 and 16, Township 39 South, Range 3 East, W.M.

Found a  $\frac{5}{8}$ " rebar, exposed 14", with aluminum cap stamped:

WEYERHAEUSER  
9  
 $\frac{1}{4}$ S —  
16  
1969  
ORLS 686

As set for corner on recorded Survey No. 4191.

- From said  $\frac{5}{8}$ " rebar with aluminum cap, the original bearing tree, now a 30" Fir bears  $S1\frac{1}{4}^{\circ}W$ , 159.7 feet to the upper face. (Original Record: 15" Fir,  $S2^{\circ}E$ , 159.7 feet (R.S. 4191 Record: White Fir,  $S2^{\circ}E$ , 159.7 feet.).
- The "W" nail set at the base of an 18" White Fir bears  $N5^{\circ}W$ , 94.38 feet. (R.S. 4191 Record: 18" White Fir,  $N7^{\circ}W$ , 94.4 feet.).

Marked new trees as follows:

- An 18" Fir, scribed CS-BT bears  $N9^{\circ}E$ , 86.5 feet to face of the lower blaze.
- A 12" Fir, scribed CS-BT bears  $S59\frac{1}{4}^{\circ}E$ , 160.2 feet to face of the lower blaze.

August 26, 1971  
Otis Blankenship  
Dan Phillips

Approved by:  
M. E. Boyden,  
County Surveyor

**SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT**

## SECOND RE-ESTABLISHMENT

GCDB 340500

Quarter corner common to Sections 9 and 16, Township 39 South, Range 3 East, W.M.

Found, at the corner, projecting 14 inches, the 5/8-inch diameter rebar with "Weyerhaeuser" aluminum cap affixed to the top, recorded as found on First re-establishment in 1971.

Removed said aluminum cap and set over top of said 5/8-inch diameter rebar, a 1 x 36-inch Galvanized iron pipe, projecting 12 inches, with a 2½-inch diameter brass cap in a mound of stones marked:

T39S R3E  
9  
¼S —  
16  
CS  
1991

"W" nail, set at the base of a White Fir, 31-inch diameter, bears N5°W, 94.4 feet. Record: Per S/N 4191; White Fir, 18-inch diameter, N7°W, 94.4 feet.

Bearing trees recorded as marked on said First re-establishment found:

- White Fir, now 26-inch diameter, with double healed blazes, bears N9°E, 87.7 feet to center of tree at lower blaze. Record: 86.5 feet to face at lower blaze.
- White Fir, now 16-inch diameter, with double healed blazes, bears S59¼°E, 160.8 feet to center of tree at lower blaze. Record: 160.2 feet to face at lower blaze.

Set new reference: Blazed and painted line, bears West, about 200 feet.

Corner lies in a wet, grassy meadow, about 250 feet West of an old dirt road.

July 10, 1991  
H. Durkee, Tech.  
T. Newcomb, Tech.

Verlyn Thomas  
County Surveyor

V = 18¼°  
P.-51