

SECOND RE-ESTABLISHMENT

GCDB 400140

Quarter corner common to Sections 33 and 34, Township 39 South, Range 3 East, W.M. $V = 18^\circ$

Found firmly set, 15 x 7 x 6-inch stone exposed 3 inches and marked "¼" on West face as recorded by F. W. Rodolf on 1917 re-establishment.

I replaced said stone with a 1 x 36-inch Galvanized iron pipe set 30 inches in the ground with a bronze disc marked:

T39S R3E
¼S
33 | 34
Jackson County 1974

Original BTs marked by E.T.T. Fisher in 1858, and noted by Rodolf in 1917 found as follows:

- The stump remains of a down and rotted Fir containing partial scribed "¼", bears Record: $S55^\circ E$, 40.92 feet.
- A Douglas Fir, 45-inch diameter, with healed blazes, bears $N70^\circ W$, 5.28 feet to estimated face of lower blaze. Re-measured 7.6 feet to center of tree at upper blaze.
- A found copper nickel pipe lies on South edge of corner.

I deposited original stone alongside corner as a memorial, marked the following trees CS BT and took measurements to center of trees at lower blaze:

- A White Fir, 10-inch diameter, bears $S78^\circ E$, 43.43 feet.
- A White Fir, 8-inch diameter, bears $N13^\circ W$, 20.55 feet.

Corner lies about 50 feet East of location marker on 18-inch diameter, Fir, alongside road.

July 31, 1974
B. Malotte
R. Frost

Approved by: Edward McGinty
County Surveyor

SEE NEXT PAGE FOR THIRD RE-ESTABLISHMENT

THIRD RE-ESTABLISHMENT

GCDB 400140

Quarter corner common to Sections 33 and 34, Township 39 South, Range 3 East, W.M.

Found 2½ ins. diameter bronze disc exposed 7 ins. on 1 ins. diameter iron pipe marked

T39S R3E
¼S
33 | 34
Jackson County 1974

with original stone found along East side.

Original bearing tree recorded in 1974 found as follows:

- Fir snag, 60 ins. diameter, with healed blazes, bears record N70°W, 7.7 feet. Bearing taken to center of upper blaze distance to side center of snag at base. 1974 Record distance 7.6 feet to center of tree at upper blaze.

New BTs marked, "CS" "BT" and measured to center of tree at base:

- White Fir, 14 ins. diameter bears N14°E, 23.80 ft.
- Douglas Fir, 20 ins. diameter bears S64°W, 34.05 ft.

Corner lies about 70 ft. West of road in heavy timber and 50 ft. West of location tag on 20 ins. diam. fir snag.

April 4, 2018
B. Paull
T. Kaiser

Scott D. Fein
Jackson County Surveyor

P. -
V=05°