

FIRST RE-ESTABLISHMENT

GCDB 400200

Section corner common to Sections 27, 28, 33 and 34, Township 39 South, Range 3 East, W.M.

Found projecting 14 inches from a mound of stones, a 1½-inch diameter iron pipe with a standard GLO brass cap marked:

T39S R3E	
S28	S27
S33	S34
1917	

Set by Fred W. Rodolf on retracement survey in 1917.

Bearing trees marked on said retracement found and measured to center at base:

- Fir, now 32-inch diameter with single healed blaze, bears Record: N42°E, 72.3 feet. Record: 71.9 feet.
- Fir, now 35-inch diameter with scribe marks including "9S R3E S3" in opened single face, bears S36¾°E, 53.1 feet. Record: (apparently transposed), S73°E, 52.1 feet.
- Fir, now 24-inch diameter with faint single healed blaze, bears S69½°W, 13.0 feet. Record: S67½°W, 13.2 feet.
- Fir, now 27-inch diameter with single healed blaze, bears N44¾°W, 20.4 feet. Record: N42°W, 19.8 feet.

Corner lies in timber on nearly level ground, an estimated 40 feet northeasterly from the northeast corner of a reforested clear-cut and an estimated 450 feet west of a location poster on a fir tree located approximately 50 feet off the west edge of a north-south paved road.

April 22, 1987
D. Edwards
T. Newcomb

Edward McGinty
County Surveyor

V = 15½°
P-115