

FIRST RE-ESTABLISHMENT

GCDB 400340

Quarter corner common to Sections 21 and 22, Township 39 South, Range 3 East, W.M.

Set a 1" x 36" galvanized iron pipe 30" in the ground with a 2½" bronze cap stamped:

T39S R3E
¼ 21 | 22 Cor. C.S.
1967

From which:

- A 24" Fir snag plainly scribed bears N51°E, 7.9 feet to the face of the lower blaze.
- A 24" Fir with scribe visible bears N76°W, 10.6 feet to the face of the lower blaze.
- Scribed a 14" Fir CS-BT which bears N39°E, 34.2 feet to the face of the lower blaze.

November 14, 1967
Gary Kaiser

L. D. Pinkham,
Deputy County Surveyor

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 400340

Quarter corner common to Sections 21 and 22, Township 39 South, Range 3 East, W.M.

Found projecting 5 inches from a mound of stones, the 1-inch diameter iron pipe with 2½-inch diameter brass cap marked:

T39S R3E
|
¼ 21 | 22 cor.
|
C.S.
1967

Reported set on First Re-establishment, page 8, in 1967.

Original bearing tree marked by Sewell Truax in 1859 found:

- Fir snag, 25-inch diameter with partial scribe mark visible in exposed face, bears Record: N76°W, 10.4 feet to said face. Record distance; 10.6 feet.

Bearing tree marked on First Re-establishment found:

- White Fir, now 19-inch diameter with double healed blazes, bears Record: N39°E, 34.90 feet to center of tree at lower blaze. Record: 34.2 feet to face.

Marked a new tree "CS" "BT":

- White Fir, 17-inch diameter, bears N62°W, 41.75 feet to center of tree at lower blaze.

Corner lies on level ground, an estimated 250 feet East of the road to Hyatt Reservoir and 50 feet South of the Pacific Crest Trail.

December 2, 1986
D. Edwards
R. Romio

Edward McGinty
County Surveyor

V = 18½°
P.-340