

FIRST RE-ESTABLISHMENT

GCDB 400500

Section corner common to Sections 9, 10, 15 and 16, Township 39 South, Range 3 East, W.M.

I locate this corner by reference to the BTs as follows:

- A 16" cedar to NE okay for distance, N50°E, for course, good condition.
- A 16" Fir to SE okay for course and distance, fair condition.
- BT to SW okay course and distance; rotted stump.
- BT to NW not identified.

I set 2" x 36" gas pipe to mark and perpetuate the corner.

From which:

- A 9" Fir, scribed CS-BT bears S17°W, 160.9 feet.
- An 18" Red Fir scribed CS-BT, bears N8¼°W, 111.6 feet.

July 28, 1938
L. E. Smith,
Deputy Surveyor

C. Bourne, Chainman

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 400500

Section corner common to Sections 9, 10, 16 and 15, Township 39 South, Range 3 East, W.M.

The 2-inch diameter gas pipe set by L. Smith on First Re-establishment in 1938 and reported on Survey No. 6103, dated 1975 was not found. Neither was the $\frac{5}{8}$ -inch diameter iron pin with "Surv KAP" set on Survey No. 4191 in 1969. Both monuments were vandalized; i.e., removed from the ground, the immediate vicinity and the mounded stones scattered.

In the hole from which the gas pipe was removed, I set a 1 x 36-inch Galvanized iron pipe with 2½-inch bronze disc marked:

Jackson County "1979"
T39S R3E
9 | 10
—|—
16 | 15

This position was confirmed from points set on Survey No. 6103 (see 1979 Jackson County Field Notes, page 1).

Original bearing trees recorded by S. Truax in 1859, found as follows:

- Cedar stump, 24-inch diameter, bears N49°E, 68.5 feet to center. Record: N54°E, 67.98 feet.
- The root hole of a tipped over Fir, 44-inch diameter, with old axed faces bears Record: N13°W, 75.24 feet.

Bearing tree marked by L. Smith in 1938:

- Douglas Fir, 36-inch diameter, scribed "CS" in exposed upper face bears N7°W, 112.14 feet to center. Record: N8¼°W, 111.6 feet.
- Slope distance to "W" nail in this tree agrees with that recorded on Survey No. 4191, 111.87 feet. Re-measured to said nail 110.66 feet.
- Reference tree recorded on Survey No. 4191, a Cedar, 14-inch diameter, with "W" nail in blazed lower face bears N53°17'E, 33.46 feet to said nail. Record: N54°E, 33.46 feet.

I mark a new tree CS BT:

- Douglas Fir, 19-inch diameter, bears N70°45'E, 42.5 feet to center of tree at lower blaze and set a lead plug in center of scribed "X" on the South face of a 4 x 3 x 1 ½ feet exposed rock, the center of said "X" bearing N24°47'W, 10.02 feet.

January 2, 1979
B. Malotte
R. Frost

Approved by: Edward McGinty
County Surveyor