

**FIRST RE-ESTABLISHMENT  
QUARTER CORNER TO SECTION 34 ONLY  
GCDB 440100**

South Quarter corner of Section 34, Township 39 South, Range 3 East, W.M.  $V = 18^\circ$

Found 1-inch diameter iron pipe, projecting 10 inches with GLO brass cap set and marked as recorded by F. W. Rodolf on 1917 resurvey:

¼S 34  
1917

BTs marked by Rodolf found as follows:

- A Douglas Fir, 60-inch diameter, with healed blaze, bears record,  $N21^\circ E$ , 34.98 feet to estimated face of blaze. Re-measured 35.3 feet to center of tree.
- A Douglas Fir, 52-inch diameter, with healed blaze, bears record,  $N34^\circ W$ , 29.7 feet to estimated face of blaze. Re-measured 31.05 feet to center of tree.
- The North ¼ of Section 3 lies 92.90 feet West. Record: 93.06 feet

I marked a new tree CS BT:

- A White Fir, 14-inch diameter, bears  $S78^\circ E$ , 49.0 feet to center of tree at lower blaze.

July 31, 1974  
B. Malotte  
R. Frost

Approved by: Edward McGinty  
County Surveyor

**SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT**

**SECOND RE-ESTABLISHMENT  
QUARTER CORNER TO SECTION 34 ONLY  
GCDB 440100**

South Quarter corner of Section 34, Township 39 South, Range 3 East, W.M.

Found 1-inch diameter iron pipe, projecting 12 inches from a mound of stone, with GLO brass cap as recorded on 1917 resurvey marked:

¼S 34  
-----  
1917

Bearing trees marked in 1917 and recorded on the First Re-establishment, dated 1974, found:

- Douglas Fir stump, with partially healed lower blaze bears 1974 record N34°W, 30.85 feet to center of stump. 1974 record distance 31.05 feet Cut in to expose partial face and axework of lower blaze.
- Douglas Fir stump, badly rotted and not remeasured. Exposed lower blaze to reveal partial scribing and reverse. Record N21°E, 35.3 feet to center of tree.
- The North quarter corner of Section 3, a GLO brass cap, bears West, 92.06 feet 1974 record, 92.90 feet. Cap marked

-----  
¼S 3  
1917

New trees marked "CS" "BT" and measured to center of tree at base:

- Douglas Fir, 16 ins. diameter bears N31½°W, 15.85 feet
- White Fir, 12 ins. diameter bears S04°E, 12.55 feet

Corner lies at edge of timber boundary approximately 350 feet West of tangent section of graveled road.

April 5, 2018  
B. Paull  
T. Kaiser

Scott D. Fein  
Jackson County Surveyor

P. -  
V. - 13°