

## FIRST RE-ESTABLISHMENT

GCDB 440300

Quarter corner common to Sections 22 and 27, Township 39 South, Range 3 East, W.M.  $V = 18\frac{3}{4}^\circ$

Found stone (20 x 10 x 8-inch) firmly set, exposed 5 inches and marked "¼" on North face, by F. W. Rodolf during 1916 retracement.

I replaced said stone with a 1 x 36-inch Galvanized iron pipe set 32 inches in the ground with a 2½-inch bronze disc marked:

T39S R3E  
¼S 22  
—  
27  
C.S.  
1973

An original BT, a Fir, now down, 21-inch diameter, containing "BT" scribed by S. Truax in 1859 and recorded by Rodolf in 1916, the stump hole of which bears record, N13°W, 15.18 feet.

I mounded stones around corner, deposited original stone alongside as a memorial and marked the following trees CS BT:

- A White Fir, 11-inch diameter, bears N66°E, 57.5 feet to center of tree at lower blaze.
- A Cedar, 11-inch diameter, bears S32°W, 21.65 feet to center of tree at lower blaze.

Corner lies approximately 430 feet East of location marker on blazed E-W line near end of road.

October 30, 1973  
B. Malotte  
R. Frost

Approved by: Edward McGinty  
County Surveyor

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

**SECOND RE-ESTABLISHMENT**

**GCDB 440300**

Quarter corner common to Sections 22 and 27, Township 39 South, Range 3 East, W.M.

Found at the corner position, exposed 4 inches in a mound of stones, the 1-inch diameter galvanized iron pipe with 2½-inch diameter brass cap set on First Re-establishment in 1973, marked:

T39S R3E  
22  
¼S —  
27  
C.S.  
1973

Bearing trees recorded on said First Re-establishment, found and measured to center of trees at lower blaze:

- Fir snag, now 19-inch Diameter with healed blazes bears Record: N 66° E, 57.5 feet.
- Cedar, now 21-inch diameter with healed blazes bears S 32° W, 21.4 feet. Record: 21.65 feet.

Marked new trees "CS" "BT" and took measurements to center of trees at lower blaze:

- White Fir 12-inch diameter bears N 76½° E, 30.2 feet.
- White Fir 5-inch diameter bears N 34° W, 46.5 feet.
- White Fir 10-inch diameter bears S 29¾° W, 95.5 feet.

Corner lies easterly approximately 450 feet from end of logging spur road.

June 16, 2005  
H. Durkee

Roger R. Roberts  
Jackson County Surveyor

P. - 79  
V. - 15°25'