

## FIRST RE-ESTABLISHMENT

GCDB 440700

Quarter corner common to Section 34, Township 38 South, Range 3 East and Section 3, Township 39 South, Range 3 East.

Set a 1"x36" galvanized iron pipe 30" in the ground with a 2½" bronze cap stamped:

T38-39SR3E  
34  
¼S — Cor.  
3  
C.S.  
1967

From which:

- A 30" Fir stump (cut by logger) with lower blaze bears S57°W, 36.3 feet to the face of the blaze;
- A 36" Fir wind-fall with "BT" scribe bears N47°W, 31.7 feet to the position of lower blaze on splintered stump.

Marked the following new trees:

- A 16" Fir scribed CS-BT bears N15°E, 11.2 feet to the face of the lower blaze;
- A 28" Fir scribed CS-BT bears N72½°W, 30.8 feet to the face.

November 7, 1967  
Gary Kaiser

L. D. Pinkham,  
Deputy County Surveyor

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

## SECOND RE-ESTABLISHMENT

GCDB 440700

Quarter corner common to Section 34, Township 38 South, Range 3 East, and Section 3, Township 39 South, Range 3 East, W.M.

Found at the corner position, exposed 4 inches and in a ring of stones, the 1-inch diameter galvanized iron pipe with 2½-inch diameter brass cap, set on First Re-establishment in 1967, marked:

T.38 - 39 S. R. 3 E.  
34  
¼S — Cor.  
3  
C.S.  
1967

Bearing trees recorded by E. T. T. Fisher in 1858, found and measured to center of tree at lower blaze:

- Sawed, rotted fir stump bears S 57° W, 36.9 feet to center of stump. Record: 36.3 feet to face.
- Fir, dead and down bears N 47° W, 32.8 feet to center of stump hole. Record: 31.7 feet to face.
- Bearing trees recorded on said First Re-establishment in 1967, found with double healed blazed and measured to center of tree at lower blaze.
- White Fir, now 22-inch diameter bears N 15° E, 11.7 feet. Record: 11.2 feet to face.
- White Fir, now 34-inch diameter bears N 71½° W, 31.9 feet. Record: 30.8 feet to face.

Marked new trees "CS" "BT" and took measurements to center of trees at lower blaze:

- Cedar 11-inch diameter bears S 7½° E, 43.4 feet.
- Cedar 20-inch diameter bears S 67½° W, 29.2 feet

Corner lies approximately 70 feet south of spur road.

May 31, 2005  
H. Durkee

Roger R. Roberts  
Jackson County Surveyor

P. - 68  
V. - 16°