

FIRST RE-ESTABLISHMENT

GCDB 500240

Quarter corner common to Sections 26 and 27, Township 39 South, Range 3 East, W.M.

Found lying alongside a mound of stones, the 1x36-inch iron pipe with standard 2-inch diameter GLO brass cap marked:

S27 | S26
¼ •
1917

With lower portion of cap having incorrect stamping obliterated.

Reset said pipe 8 inches in ground with said mound, and rebuild mound.

Original bearing tree marked by Fred W. Rodolf in 1917 found:

- White Fir, now 43-inch diameter with single healed blaze, bears N25°E, 15.2 feet to center of tree near base. Record: N35°E.
- Original blazed line bears North from corner.

Marked a new tree "CS" "BT":

- White Fir, 24-inch diameter bears N28°W, 37.87 feet to center of tree at lower blaze.

Corner lies 60 feet East of a gravel road, bearing N20°W and S20°E.

April 22, 1987
D. Edwards
T. Newcomb

Edward McGinty
County Surveyor

V = 15°
P.-117

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 500240

Quarter corner common to Section 26 and 27, Township 39 South, Range 3 East, W.M.

Found dislodged and laying in adjacent brush, the 1 x 36-inch Galvanized iron pipe with standard GLO 2-inch diameter brass cap set by Fred Rodolf in 1917, marked:

S27 | S26
¼ •
1917

From the following evidence, reset said monument at the correct position, 20 inches in the ground and in a mound of stones 3 feet x 4 feet x 16 inches high.

- Single remaining bearing tree recorded by Fred W. Rodolf in 1917, a White Fir, now 43-inch diameter with healed single blaze bears N25°E, 15.2 feet to center of tree at base. Record: N35°E.
- Bearing tree recorded on First Re-Establishment in 1987, a White Fir, now 26-inch diameter with double healed blazes, bears Record: N28°W, 37.9 feet to center of tree at lower blaze.

Marked new bearing tree "CS" "BT" and take measurement to center of tree at lower blaze:

- White Fir, 6-inch diameter bears S62°E, 8.8 feet.
- No other trees available within reasonable limits.

Corner lies east, approximately 50 feet from graveled road.

June 22, 2005
H. Durkee

Roger R. Roberts
Jackson County Surveyor

P. - 84
V. - 15°20'