

**FIRST RE-ESTABLISHMENT**

**GCDB 500340**

Quarter corner common to Sections 22 and 23, Township 39 South, Range 3 East, W.M.  $V = 18\frac{1}{2}^\circ$

Found in a mound of stone, a  $\frac{5}{8}$ -inch steel rod, projecting 6 inches with aluminum cap marked:

WEYERHAEUSER  
 $\frac{1}{4}$   
22 | 23  
1969  
ORLS 686

From which:

- The stump hole of original NE BT, with rotted section of Fir alongside containing scribed " $\frac{1}{4}$ " and partial "S", bears Record: N45°E, 41.58 feet.
- Over aforementioned  $\frac{5}{8}$  inches rod, I drove a 1 x 36-inch Galvanized iron pipe 24 inches in the ground with a 2½-inch bronze disc marked:

T39S R3E  
 $\frac{1}{4}$ S  
22 | 23  
C.S.  
1973

I marked the following trees CS BT and take bearings and distances to the head of nail (marked "W") at the base of each tree:

- A White Fir, 20-inch diameter, bears S85°E, 15.18 feet.
- A Douglas Fir, 18-inch diameter, bears N6°W, 5.74 feet.

Corner lies at North edge of clearing.

October 31, 1974  
B. Malotte  
R. Frost

Approved by: Edward McGinty  
County Surveyor