

FIRST RE-ESTABLISHMENT

GCDB 500400

Corner common to Sections 14, 15, 22 and 23, Township 39 South, Range 3 East, W.M.

Found a 5/8" rebar exposed 12" with 1 1/2" aluminum cap stamped:

WEYERHAEUSER
T39S R3E
15 | 14
Sec. ———— Cor.
22 | 23
1969
ORLS 686

For corner.

From which:

- The original bearing tree (now a 24" White Fir with healed blazes), bears S30°E, 9.2 feet to center of the tree. Record: 4" Fir, S29°E, 9.2 feet.
- The original bearing tree, (now a 34" dead Fir snag with upper face open and scribe "S 14" visible), bears N51°E, 11.6 feet to the upper face. Record: 24" Fir, N48°E, 11.2 feet.
- The original bearing tree, (now a 31" White Fir with healed blazes), bears N78 1/4°W, 25.1 feet to center of the tree. Record: 15" Fir, N80°W, 24.4 feet.
- The original bearing tree (now a 48" Cedar with healed blazes), bears S21 3/4°W, 99.5 feet to center of the tree. Record: 28" Cedar, S21°W, 97.7 feet.

Marked the following new tree:

- A 10" White Fir scribed "CS-BT" bears N6 3/4°E, 41.2 feet to face of the lower blaze.

August 19, 1971
Otis Blankenship
Lloyd Shreeve

Approved by:
M. E. Boyden,
County Surveyor

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 500400

Section corner common to Sections 14, 15, 22 and 23, Township 39 South, Range 3 East, W.M.

Found projecting 10 inches, a $\frac{5}{8}$ -inch rebar with aluminum survey cap, set on Survey No. 4192, dated 1969, marked as shown on said survey and reported on First Re-establishment, dated 1971.

Removed cap and set a 1x36-inch Galvanized iron pipe over $\frac{5}{8}$ -inch rebar 30 inches in the ground with a 2½-inch diameter brass cap marked:

	T39S	R3E	
	15	14	
Sec.	22	23	Cor.
	CS		
	1991		

Original bearing trees reported by Sewall Truax in 1857 found with healed blazes and measured to the center of tree at lower blaze:

- White Fir, 44-inch diameter, bears Record: (1971) N78¼°W, 25.10 feet.
- White Fir, 24-inch diameter, bears Record: (1971) S30°E, 9.20 feet.

Bearing tree found on First Re-establishment found:

- White Fir, 11-inch diameter, with healed blazes, bears N6¾°E, 41.40 feet to the center of tree at lower blaze. Record: 41.20 feet

Marked new tree "CS" "BT":

- White Fir, 16-inch diameter, bears S31°W, 16.20 feet to the center of tree at lower blaze.

Corner lies in heavy timber and ground cover with very little brush and level. Original blazed line found N-S-E and W from corner.

February 1, 1991
T. Newcomb, Tech.
H. Durkee, Tech.

Verlyn Thomas
County Surveyor

V = 18¼°
P.-9