

GCDB 500440 AND 500449

FIRST RE-ESTABLISHMENT

QUARTER CORNER

GCDB 500440

Quarter corner common to Sections 14 and 15, Township 39 South, Range 3 East, W.M.

Set a 1" x 36" galvanized iron pipe 32" in the ground with a 2½" bronze cap stamped:

T39S R3E
¼ 15 | 14 Cor.
C.S.
1967

From which:

- A 36" Fir, plainly scribed, bears East 2.6 feet to the face of the upper blaze.

Marked a new tree:

- A 20" Fir scribed CS-BT bears N26°W, 45.0 feet to the face of the upper blaze.

November 13, 1967
Gary Kaiser

L. D. Pinkham,
Deputy County Surveyor

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT TO QUARTER CORNER

**SECOND RE-ESTABLISHMENT
QUARTER CORNER
GCDB 500440**

Quarter corner common to Sections 14 and 15, Township 39 South, Range 3 East, W.M.

Found 1-inch Galvanized iron pipe with attached 2½-inch bronze cap marked:

T39S R3E
¼ 15 | 14 Cor.
C.S.
1967

Set on First Re-establishment.

Recorded BTs (1967) found as follows:

- A White Fir, now a snag 20-inch diameter, containing scribed "CS" and "BT", bears record, N26°W, 45.0 feet to scribed face.
- A Fir, 36-inch diameter, with partially exposed face bears Record: East, 2.6 feet to face.

I marked a new tree CS BT":

- A White Fir, 12-inch diameter, bears N47½°W, 31.25 feet to center of tree at lower blaze.

Corner lies approximately 30 feet North of road.

October 31, 1973
B. Malotte
R. Frost

Approved by: Edward McGinty
County Surveyor

SEE NEXT PAGE FOR FIRST RE-ESTABLISHMENT OF WITNESS CORNER

**FIRST ESTABLISHMENT
WITNESS CORNER TO 500440
GCDB 500449**

Witness corner common to Sections 14 and 15, Township 39 South, Range 3 East, W.M.

Set on line between the section corner of 10, 11, 14 and 15 and the ¼ corner of 14 and 15, a 1 x 36-inch Galvanized iron pipe 36 inches in the ground with a 2½-inch diameter brass cap marked:

T39S R3E
Wit. 15 | 14 Cor.
C.S.
1992

- Section corner bears N0°27'59"W, 603.88 feet.
- Set a 5/8 x 24-inch rebar with aluminum cap marked "Jackson County CS" projecting 3 inches, bears S0°27'59"E, 86.24 feet.

Marked bearing trees "CS" "BT" and took measurements to the center of tree at lower blaze:

- White Fir, 21-inch diameter, bears S61°10'49"E, 19.80 feet.
- White Fir, 18-inch diameter, bears S49°21'59"W, 29.50 feet.

Note: In 1922, F. H. Walker set near this same position, but no field notes were found in the City Engineers Office in Ashland. Found cruiser marks "K" on the bearing tree we marked to the SW, no other evidence found.

Set 5½ feet long steel fence post East side of corner.

October 12, 1992
T. Newcomb, Tech.
J. Burgess

Verlyn Thomas
County Surveyor

P.-108

SEE Job File No. 92-7.

NOTE: 8/16/95

Field notes of Walkers found in M. E. Boyden's files in 8/7/95. These notes are now in Job File No.92-7. Found all 4 of Walkers bearing trees and the position established by Walker bears N36°E, 6.60 feet. Hand compass bearing.

Note: None of the bearing trees were scribed. (T. Newcomb)