

**FIRST RE-ESTABLISHMENT
QUARTER CORNER AND WITNESS CORNER
GCDB 500540 AND 500530**

Quarter section corner common to Sections 10 and 11, Township 39 South, Range 3 East, W.M.

Found

- A pointed square stake below the surface of the ground at the corner.
- Also the original BT, a dead Pine, with a portion of the BT scribe visible which tree bears East 76.56 feet.

Set an 8" x 10" x 16" basalt stone marked with an X on top and $\frac{1}{4}$ on East face set 12" in the ground for corner.

Also find the witness corner as reported by Surveyor F. H. Walker, set October 30, 1922, said witness corner being marked.

Two Fir snags scribed from which snags

- Found the old stake corner below the surface of the ground which I replaced with a 1" x 36" galvanized iron pipe set 30" in the ground for corner.

From which:

- An 18" White Fir scribed CS-BT bears S46°E, 55.6 feet.
- A 12" White Fir scribed CS-BT bears S44½°W, 90.5 feet.

The said witness corner was found to be 632.8 feet magnetic course South (21°E. Var.) from the $\frac{1}{4}$ corner to Sections 10 and 11 which agrees with Surveyor F. H. Walker's report.

August 19, 1955
C. Z. Boyden
John C. Warnkee

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT OF WITNESS CORNER

**SECOND RE-ESTABLISHMENT
WITNESS CORNER ONLY
GCDB 500530**

Quarter corner common to Sections 10 and 11, Township 39 South, Range 3 East, W.M.

Found the 1" galvanized iron pipe witness corner monument and the two established witness trees for the witness corner as monumented on August 19, 1955 by Deputy County Surveyor C. Z. Boyden.

Set a 2½" brass cap in the top of said 1" corner pipe monument stamped:

T39S R3E
Witness Cor.
632.8' South
of ¼ cor.
Sections 10 & 11
CS 1961

With the top 2" above the level of the beach.

From which:

- An 18" White Fir, dead, plainly scribed CS-BT bears S44½°E, 55.7 feet to the face of the lower blaze.
- A 12" White Fir, plainly scribed CS-BT bears S35°W, 90.2 feet to the face of the upper blaze. (This tree was erroneously reported to bear S44½°W.)

I mark the following new trees:

- An 11" White Fir, scribed CS-BT bears S76°E, 107.4 feet to the face of the lower blaze.
- A 14" White Fir, scribed CS-BT bears S36°E, 116.4 feet to the face of the lower blaze.

Note: The waters of Hiatt Lake have submerged the ¼ corner stone.

Var. 20° East
June 21, 1961
M. E. Boyden, County Surveyor
N. A. Newton

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT OF QUARTER CORNER

**SECOND RE-ESTABLISHMENT
QUARTER CORNER ONLY
GCDB 500540**

Quarter corner common to Sections 10 and 11, Township 39 South, Range 3 East, W.M.

- Found a basalt stone 10 x 10 x 6-inch projecting 5 inches marked with "+" on top and "¼" on East face.
- Also a very rusty 1-inch diameter pinched top pipe .50 feet Northerly from stone.

Replaced stone with and lay alongside a 1 x 36-inch Galvanized iron pipe 30 inches in the ground with a 2½-inch diameter brass cap marked:

T39S R3E
¼S
10 | 11
C.S.
1992

Original bearing tree marked by Sewall Truax in 1859 found:

- Rotted stump bears Record: East, 76.56 feet to estimated face.
- Witness corner, 2½-inch brass cap set on Second re-establishment dated 1961, bears S0°04'48"E, 632.80 feet. Record: South.
- Set a 2½-inch diameter axle 27 inches long with a 9½-inch bolt plate set 24 inches in the ground bears S16°29'E, 39.65 feet.
- Set a 2½-inch diameter axle 24 inches long with a 9½-inch bolt plate set 19 inches in the ground, bears S37°05'W, 35.75 feet.
- Dry dock bears S44°17'E, 35.00 feet.

Corner lies in reservoir, presently dry.

September 2, 1992
T. Newcomb, Tech.
J. Burgess

Verlyn Thomas
County Surveyor

V = 17¾°
P.-83

SEE job file No. 92-7

SEE NEXT PAGE FOR THIRD RE-ESTABLISHMENT OF WITNESS CORNER

**THIRD RE-ESTABLISHMENT
WITNESS CORNER ONLY
GCDB 500530**

Witness corner common to Sections 10 and 11, Township 39 South, Range 3 East, W.M.

Found 2 inches deep, the 2½-inch diameter brass cap set on Second re-establishment, dated 1961 marked:

T39S R3E
Witness Cor.
CS
632.8
South
1961

Bearing tree marked on First re-establishment, dated 1955 found:

- A White Fir, 20-inch diameter, with healed blazes, bears record, (1961) S35°W, 90.20 feet to estimated face. Re-measured to the center of tree at lower blaze, 90.70 feet.

Bearing trees marked on Second re-establishment with healed blazes found:

- White Fir, 17-inch diameter, S77°E, 107.40 feet to estimated face. Record: S76°E. Re-measured to the center of tree at lower blaze, 107.85 feet.
- White Fir, 22-inch diameter, bears Record: S36°E, 116.40 feet to estimated face. Re-measured to the center of tree at lower blaze, 117.00 feet.

Set flush a 5/8 x 24-inch rebar with aluminum cap marked "Jackson County CS" bears S0°04'49"E, 53.72 feet. Rebar is on line and in lawn of residence to the East.

Corner lies about 44 feet West of high water mark.

September 2, 1992
T. Newcomb, Tech.
J. Burgess

Verlyn Thomas
County Surveyor

V = 17½°
P.-111

SEE Job File No. 92-7