

## FIRST RE-ESTABLISHMENT

GCDB 500700

Corner common to Sections 34 and 35, Township 38 South, Range 3 East and Sections 2 and 3, Township 39 South, Range 3 East.

Set a 1"x36" galvanized iron pipe 28" in the ground with a 2½" bronze cap stamped:

|      |            |    |      |
|------|------------|----|------|
|      | T38-39SR3E |    |      |
|      | 34         | 35 |      |
| SEC. | 3          | 2  | COR. |
|      | C.S.       |    |      |
|      | 1967       |    |      |

From which:

- A 30" Fir plainly scribed bears North  $26\frac{1}{2}^{\circ}$  East, 30.0 feet to the face of the upper blaze;
- A 20" Fir plainly scribed bears South  $3\frac{1}{2}^{\circ}$  East, 9.3 feet to the face of the upper blaze;
- A 26" Fir plainly scribed bears South  $42\frac{1}{2}^{\circ}$  West, 15.0 feet to the face of the upper blaze;
- The stump hole of a down and badly rotted fir snag, with a pitched slab plainly scribed, bears South  $68^{\circ}$  West, 23.0 feet to the center.
- Scribed a 28" Fir CS-BT which bears North  $21^{\circ}$  West, 48.3 feet to the face of the lower blaze.

November 7, 1967

Gary Kaiser

L. D. Pinkham,  
Deputy County Surveyor


SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

## SECOND RE-ESTABLISHMENT

GCDB 500700

Section corner common to Sections 34 and 35, Township 38 South and Sections 2 and 3, Township 39 South, Range 3 East, W.M.

Found at the corner position, exposed 6 inches and in a mound of stones, the 1-inch diameter galvanized iron pipe with a 2½-inch diameter brass cap set on First Re-establishment in 1967, mismarked:



Original bearing trees recorded by Sewall Truax of the GLO in 1859, found with healed blazes and measured to center of trees at base:

- Fir snag bears N26½°E, 30.8 feet. Record: 30.0 feet to face.
- White Fir, now 28-inch diameter bears S3½°E, 9.7 feet. Record: 9.3 feet to face.
- Fir snag bears S42½°W, 15.6 feet. Record: 15.0 feet to face.

Bearing tree recorded on First Re-establishment in 1967, found with healed double blazes and measured to center of tree at base:

- White Fir, now 33-inch diameter bears N21°W, 49.5 feet. Record: 48.3 feet to face.

Marked new bearing trees "CS" "BT" and took measurements to center of trees at lower blaze:

- White Fir 12-inch diameter bears N41½°E, 23.2 feet.
- White Fir 22-inch diameter bears S3¼°W, 35.7 feet.

Corner lies approximately 250 feet easterly of gravel road.

October 3, 2006

H. Durkee  
B. Beeman  
S. Fein

Roger R. Roberts  
Jackson County Surveyor

P. - 170  
V. - 15°25'