

FIRST RE-ESTABLISHMENT

GCDB 540400

Quarter corner common to Sections 14 and 23, Township 39 South, Range 3 East, W.M. $V = 18^\circ$

In a found mound of stone, I set a 1 x 36-inch Galvanized iron pipe 12 inches in the ground with a 2½-inch bronze disc marked:

T39S R3E
14
¼S —
23
C.S.
1973

From which:

- An original BT., marked by S. Truax in 1859, a Cedar now 26-inch diameter, containing chaining notch and partial scribed "BT" in partly open face, bears Record: $N5^\circ E$, 178.2 feet.
- The Oak stump remains of original SW BT bears Record: $S49^\circ W$, 17.82 feet.

I mounded stones around corner, marked the following trees CS BT and took measurements to center of trees at lower blaze:

- A Cedar, 18-inch diameter, bears $N54\frac{1}{2}^\circ E$, 191.2 feet.
- A White Fir, 16-inch diameter, bears $S19\frac{1}{2}^\circ E$, 29.65 feet.

Corner lies in large opening, approximately 1,300 feet East of location marker on 36-inch diameter Cedar alongside road.

October 31, 1973
B. Malotte
R. Frost

Approved by: Edward McGinty
County Surveyor

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 540400

Quarter corner common to Sections 14 and 23, Township 39 South, Range 3 East, W.M.

Found at the corner position, exposed 20 inches and in a large mound of stones, the 1-inch diameter galvanized iron pipe with a 2½-inch diameter brass cap, set on First Re-establishment in 1973, marked:

T39S R3E
14
¼S —
23
C.S.
1973

Single remaining bearing tree recorded by S. Truax in 1859, a cedar, now 30-inch diameter with opened and rotted face bears Record: N5°E, 178.2 feet to center of tree.

Bearing trees recorded on said First Re-establishment, found and measured to center of trees at lower blaze:

- Cedar, now 24-inch diameter with healed double blazes bears Record: N54½°E, 191.2 feet.
- White Fir snag, now 26-inch diameter with healed double blazes bears Record: S19½°E, 29.65 feet.

Marked new bearing trees "CS" "BT" and took measurements to center of trees at lower blaze:

- White Fir 15-inch diameter bears S7¼°W, 19.3 feet.
- White Fir 16-inch diameter bears S74°W, 31.4 feet.

Corner lies northwesterly approximately 800 feet from end of spur road on northeasterly slope near top of ridge.

June 21, 2005

H. Durkee

Roger R. Roberts
Jackson County Surveyor

P. - 83
V. - 15°