

FIRST RE-ESTABLISHMENT

GCDB 540600

Quarter corner common to Sections 2 and 11, Township 39 South, Range 3 East, W.M.

Set a 1" x 36" galvanized iron pipe 28" in the ground with a 2½" bronze cap stamped:

T39S R3E
2
¼S — COR.
11
C.S.
1967

From which:

- A 24" Fir snag plainly scribed bears N47°W, 42.2 feet.
- A 48" Fir stump, too badly rotted to find a scribe, bears S43°E, 17.8 feet to the face of the tree.

Marked the following new trees:

- A 14" Fir scribed CS-BT bears N63°E, 15.5 feet to the face of the upper blaze.
- A 12" Fir scribed CS-BT bears S3°E, 26.8 feet to the face of the upper blaze.

November 14, 1967
Gary Kaiser

L. D. Pinkham,
Deputy County Surveyor

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 540600

Quarter corner common to Sections 2 and 11, Township 39 South, Range 3 East, W.M.

Found at the corner position, exposed 6 inches in a mound of stones, the 1-inch diameter galvanized iron pipe with a 2½-inch diameter brass cap, set on First Re-establishment in 1967, marked:

T. 39 S. R. 3 E.
2
¼S — COR.
11
C.S.
1967

Bearing trees recorded by E. T. T. Fisher in 1858, found and measured to center of trees at lower blaze:

- Fir snag 24-inch diameter, dead and down, bears N 47° W, 43.1 feet to center of stump hole. Record: 42.2 feet to face.
- Sawed, rotted fir stump, 48-inch diameter, bears S 43° E, 19.3 feet to center of stump. Record: 17.8 feet to face.

Bearing trees recorded on said First Re-establishment, found and measured to center of trees at lower blaze:

- Fir snag, 19-inch diameter with healed double blazes, bears N 63° E, 16.1 feet. Record: 15.5 feet to face.
- Fir, now 15-inch diameter with healed double blazes, bears S 3° E, 27.1 feet. Record: 26.8 feet to face.

Marked new trees "CS" "BT" and took measurements to center of trees at lower blaze:

- White Fir 7-inch diameter bears N 2½° E, 12.3 feet.
- White Fir 9-inch diameter bears N 46¾° W, 14.0 feet.
- White Fir 7-inch diameter bears S 23° W, 14.4 feet.

Corner lies atop a knob approximately 1000 feet north of spur road.

June 1, 2005
H. Durkee

Roger R. Roberts
Jackson County Surveyor

P. - 71
V. - 16°15'