


## FIRST RE-ESTABLISHMENT

GCDB 600300

Section corner common to Sections 23, 24, 25 and 26, Township 39 South, Range 3 East, W.M.

Found projecting 23 inches in a mound of stones, the 1½-inch diameter iron pipe with standard GLO brass cap marked:



Bearing trees marked by Fred W. Rodolf in 1917 found and measured to center of trees near base:

- Fir snag, now 35-inch diameter with partial scribe mark visible in partially healed single blaze, bears N77½°E, 22.9 feet. Record: N84°E, 22.4 feet.
- Fir, now 40-inch diameter with single healed blaze, bears Record: S75°E, 30.4 feet. Record: Distance 30.9 feet.
- Fir, now 42-inch diameter with single healed blaze, bears S20¾°W, 27.6 feet. Record: S21°W, 27.1 feet.
- Sugar Pine, now 61-inch diameter with single healed blaze, bears N55°W, 19.7 feet. Record: N57°W, 19.80 feet.

Rebuild mound of stones and scribe a new tree "CS" "BT":

- Fir, 15-inch diameter, bears N27½°E, 31.5 feet to center of tree at lower blaze.

Corner lies N10°E, an estimated 100 feet from a road intersection, courses N65°W and N35°W and an estimated 200 feet south of the middle of a high tension power line, course N80°W.

April 27, 1987  
D. Edwards  
T. Newcomb

Edward McGinty  
County Surveyor

V = 17½°

P.-129