

## FIRST RE-ESTABLISHMENT

GCDB 600500

Section corner common to Sections 11, 12, 13 and 14, Township 39 South, Range 3 East, W.M.

Set a 1" x 36" galvanized iron pipe 34" in the ground with a 2½" bronze cap stamped:

	T39S R3E	
	11   12	
Sec.		Cor.
	14   13	
	C.S.	
	1967	

From which:

- The snag stump of a 36" Fir plainly scribed bears S44°W, 2.0 feet to the face of the lower blaze.
- A 24" Fir wind fall with old scar and BLM tag, bears N57°W, 29 feet to the center of a large stump hole.

Marked the following new trees:

- A 14" Fir scribed CS-BT bears S82½°E, 64.4 feet to the face of the lower blaze.
- A 20" Fir scribed CS-BT bears S87°W, 48.5 feet to the face of the lower blaze.
- An 8" Fir scribed CS-BT bears N27½°E, 26.4 feet to the face of the upper blaze.
- A 26" Fir scribed CS-BT bears N25°W, 45.4 feet to the face of the upper blaze.

Weyerhaeuser Timber County has several reference spikes set in the trees near this corner.

November 13, 1967  
Gary Kaiser  
L. D. Pinkham,  
Deputy County Surveyor

**SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT**

## SECOND RE-ESTABLISHMENT

GCDB 600500

Section corner common to Sections 11, 12, 13 and 14, Township 39 South, Range 3 East, W.M.

At the corner, found projecting 2 inches, in ring of stone, the 1-inch diameter galvanized iron pipe, with 2½-inch diameter brass cap marked:

	T39S R3E	
	11   12	
Sec.		Cor.
	14   13	
	C.S.	
	1967	

On First Re-establishment in 1967.

Original bearing trees marked by S. Truax in 1859 found:

- Rotted fir stob (with section alongside containing scribe marked) bears Record: S44°W, 1.98 feet to estimated original position of scribed face.
- The base of a down and rotted fir, about 24-inch diameter, bears Record: N57°W, 28.38 feet.

Bearing trees marked on First Re-establishment re-measured to center of trees at lower blaze:

- White Fir, 14-inch diameter, with healed blazes, bears N27½°E, 26.80 feet. Record: 26.4 feet.
- Douglas Fir, 21-inch diameter, with healed blazes, bears S82½°E, 64.98 feet. Record: 64.4 feet.
- Douglas Fir, 30-inch diameter, with healed blazes, bears S87°W, 49.33 feet. Record: 48.5 feet.
- Fir snag, 29-inch diameter, scribed "CS" "BT" in exposed faces, bears N25°W, 46.05 feet. Record: 45.4 feet.

Marked a new tree "CS BT":

- White Fir, 10-inch diameter, bears N68½°W, 40.17 feet to center of tree at lower blaze.

Corner lies on North (25%) slope, about 600 feet South of location marker on 25-inch diameter Fir alongside road C. East-West.

August 1, 1983  
R. Frost  
B. Malotte

Edward McGinty  
County Surveyor

V = 18°  
P.-71


SEE NEXT PAGE FOR THIRD RE-ESTABLISHMENT

### THIRD RE-ESTABLISHMENT

GCDB 600500

Section corner common to Sections 11, 12, 13 and 14, Township 39 South, Range 3 east, W.M.

Found at the corner position, exposed 3 inches and in a mound of stones, the 1-inch diameter galvanized iron pipe with a 2½-inch diameter brass cap, set on First Re-establishment in 1967, marked:



Single remaining original bearing tree recorded by Sewall Truax of the GLO in 1859,

- Rotted fir remains with a weathered face bears Record: S 44° W, 2.0 feet to center of stump hole.

Bearing trees recorded on First Re-establishment in 1967 found with healed double blazes and measured to center of tree at lower blaze:

- White Fir, now 21-inch diameter bears N 27½° E, 27.3 feet. Record: 26.8 feet.
- Douglas Fir snag bears Record: S 82½° E, 65.0 feet.
- Douglas Fir, now 36-inch diameter bears S 87° W, 49.7 feet. Record: 49.3 feet.
- Fir snag, down and rotted, not measured due to dense brush. Record: N 25° W, 46.1 feet.

Bearing tree recorded on Second Re-establishment in 1983:

- A Douglas Fir snag with double healed blazes bears Record: N 68½° W, 40.2 feet.

Marked new bearing trees "CS" "BT" and took measurements to center of trees at lower blaze:

- Cedar 8-inch diameter bears N 45½° W, 12.0 feet.
- Cedar 9-inch diameter bears S 3¼° E, 13.4 feet.

Corner lies approximately 600 feet south of a locked gate.

September 28, 2006

H. Durkee

B. Beeman

Roger R. Roberts

Jackson County Surveyor

P. - 169

V. - 15°