

FIRST RE-ESTABLISHMENT

GCDB 600540

Quarter corner common to Sections 11 and 12, Township 39 South, Range 3 East, W.M. $V = 18\frac{1}{2}^\circ$

Found copper-nickel pipe, $\frac{1}{2}$ -inch diameter, projecting 12 inches in a mound of stone on blazed North-South line.

I replaced said pipe with a 1 x 36-inch Galvanized iron pipe set 30 inches in the ground with a 2 $\frac{1}{2}$ -inch bronze disc marked:

T39S R3E
 $\frac{1}{4}$ S
 11 | 12
Jackson County 1974

Original BTs recorded by S. Truax in 1859 found as follows:

- A White Fir, 26-inch diameter, with healed blazes, bears Record: S36°E, 45.54 feet on slope, to estimated face of blaze. Re-measured 45.5 feet to center of tree.
- A White Fir, 12-inch diameter, with healed blazes, bears record, S34°W, 21.12 feet to estimated face of blaze. Re-measured 21.5 feet to center of tree.

I drove found pipe alongside corner and marked a new tree CS BT:

- A White Fir, 9-inch diameter, bears N15 $\frac{1}{2}$ °W, 10.22 feet to center of tree at lower blaze.

Corner lies 10 feet West of skid road, C-South.

July 23, 1974
B. Malotte
R. Frost

Approved by: Edward McGinty
County Surveyor