

FIRST RE-ESTABLISHMENT

GCDB 600600

Section corner common to Sections 1, 2, 11 and 12, Township 39 South, Range 3 East, W.M.

Found a 5/8" nickel tubing for the corner and replaced same with a 1" x 36" galvanized iron pipe set 30" in the ground with a 2½" bronze cap stamped:

	T39S	R3E	
	2	1	
SEC.			COR.
	11	12	
	C.S.		
	1967		

From which:

- A 30" Fir with blazes intact bears N30°E, 8.5 feet to the face of the tree.
- A 12" Fir stump plainly scribed bears N45°W, 6.6 feet to the face of the lower blaze.
- A 12" Fir snag plainly scribed bears S50°W, 12.5 feet to the face of the upper blaze.
- **Note:** These trees marked "R4E" for wrong Township.

Marked the following new trees:

- A 30" Fir scribed CS-BT bears S65°W, 38.0 feet to the face of the lower blaze.
- A 40" Fir scribed CS-BT bears S74°E, 23.3 feet to the face of the lower blaze.
- A 10" Fir scribed CS-BT bears N½°W, 19.0 feet to the face of the upper blaze.

November 14, 1967

Gary Kaiser

L. D. Pinkham,
Deputy County Surveyor

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 600600

Section corner common to Sections 1, 2, 11 and 12, Township 39 South, Range 3 East, W.M.

Found at the corner position, exposed 6 inches in a ring of stones, the 1-inch diameter galvanized iron pipe with a 2½-inch diameter brass cap set on First Re-establishment in 1967, marked:

T. 39 S. R. 3 E.	
2	1
Sec. ———	Cor.
11	12
C.S.	
1967	

Original bearing trees recorded by E. T. T. Fisher in 1858 found and measured to center of tree at lower blaze:

- Fir snag, 12-inch diameter with opened upper face revealing scribe marks "9 R4E S1" bears S 49° W, 12.9 feet. Record: S 50° W, 12.5 feet to face.
- Fir snag, 32-inch diameter with healed double blazes, bears N 30° E, 9.6 feet. Record: 8.5 feet to face.

Bearing trees recorded on said First Re-establishment, found and measured to center of trees at lower blaze:

- Fir snag, 32-inch diameter with healed double blazes bears S 65° W, 39.2 feet. Record: 38.0 feet to face.
- Fir, now 42-inch diameter with healed double blazes bears S 74° E, 25.2 feet. Record: 23.3 feet to face.
- Sawed fir stump, 20-inch diameter bears N ½° W, 19.2 feet to center of stump. Record: 19.0 feet to face.

Marked new trees "CS" "BT" and took measurements to center of trees at lower blaze:

- White Fir 11-inch diameter bears N 68½° W, 56.7 feet.
- White Fir 15-inch diameter bears N 44½° E, 48.4 feet.

Corner lies approximately 500 feet ENE of end of spur road.

June 1, 2005
H. Durkee

Roger R. Roberts
Jackson County Surveyor

P. - 70
V. - 16°