

FIRST RE-ESTABLISHMENT

GCDB 600640

Quarter corner common to Sections 1 and 2, Township 39 South, Range 3 East, W.M.

Found both original witness trees.

Set a 1" x 36" galvanized iron pipe with bronze cap stamped:

T39S R3E
¼ Cor. 2 | 1 C.S.
1962

30" in the ground for corner.

From which:

- The original witness tree (now a 16" Fir) with old faces bears N48°E, 6.3 feet to the center of the tree.
- The original witness tree (now a Fir snag with scribe marks visible) bears S45°W, 19.1 feet to the lower face.
- Scribed a 10" White Fir, CS-BT, which bears N10°W, 19.2 feet.
- Scribed a 6" Fir, CS-BT, which bears S70½°W, 14.4 feet.

October 29, 1962
F. A. Roberts
L. Hart

Approved by:
M. E. Boyden,
County Surveyor

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 600640

Quarter corner common to Sections 1 and 2, Township 39 South, Range 3 East, W.M.

Found at the corner position, exposed 2 inches and in a ring of stones, the 1-inch diameter galvanized iron pipe with a 2½-inch diameter brass cap set on First Re-establishment in 1962, marked:

T39S R3E
¼ S2 • S1 COR.
C.S. 1962

Bearing trees recorded on said First Re-establishment, found with healed double blazes and measured to center of trees at lower blaze:

- White Fir, now 18-inch diameter bears N8°W, 19.2 feet. Record: N10°W.
- White Fir, now 12-inch diameter bears Record: S70½°W, 14.4 feet.

Marked new bearing trees "CS" "BT" and took measurements to center of trees at lower blaze:

- White Fir 9-inch diameter bears N48°E, 29.0 feet.
- White Fir 6-inch diameter bears N54°W, 49.2 feet.

Corner lies approximately 350 feet west of graveled spur road.

May 18, 2005

H. Durkee

Roger R. Roberts
Jackson County Surveyor

P. - 58
V. - 15°