

## FIRST RE-ESTABLISHMENT

GCDB 640100

Quarter corner common to Sections 36 and 1, Townships 39 and 40 South, Range 3 East, W.M.  
V = 21°

Found  $\frac{5}{8}$ -inch diameter, steel rod projecting 18 inches in a pile of stones with aluminum cap marked:

WEYERHAEUSER  
36  
 $\frac{1}{4}$ S —  
1  
1973  
ORLS 686

I replaced said rod with a 1" x 36" Galvanized iron pipe set 20 inches in the ground with a 2½-inch bronze disc marked:

T39S R3E  
36  
 $\frac{1}{4}$ S —  
1  
T40S  
C.S.  
1973

From which original BTs (erroneously identified as Cedar by E.T.T. Fisher in 1858) are found as follows:

- A Juniper snag, 15-inch diameter, containing chaining notch and scribed " $\frac{1}{4}$ S" and "BT" in exposed blaze, bears S57°E, 24.6 feet to scribed blaze. Record: S57°E, 24.42 feet.
- A Juniper, 20-inch diameter, containing chaining notch and scribed " $\frac{1}{4}$ S" and "BT" on exposed blaze, bears N70°W, 7.03 feet to scribed blaze. Record: N70°W, 6.6 feet.
- Round headed nail with head marked "W" found in base of each of above trees.

I marked following trees CS BT and took measurements to center of trees at lower blaze:

- A Juniper, 9-inch diameter, bears N27½°E, 28.1 feet.
- A Juniper, 14-inch diameter, bears S45°E, 34.9 feet.

Corner lies approximately 350 feet East of canal Road

October 5, 1973  
B. Malotte  
R. Frost

Approved by: Edward McGinty  
County Surveyor