

**FIRST RE-ESTABLISHMENT**

**GCDB 640300**

Quarter corner common to Sections 24 and 25, Township 39 South, Range 3 East, W.M.  $V = 20\frac{1}{2}^\circ$

Found 5/8-inch steel rod projecting 15 inches in a pile of stones, with aluminum cap marked:

Weyerhaeuser  
24  
¼S —  
25  
1972  
ORLS 686

I replaced said rod with a 1 x 36-inch Galvanized iron pipe set 30 inches in the ground with a 2½-inch bronze disc marked:

T39S R3E  
24  
¼S —  
25  
C.S.  
1973

From which:

- An original BT., now a rotted Fir stump, fragments of which contain scribed "BT", bears S15°E, 21.12 feet. Record: S5°E, 21.12 feet.
- An original BT, now a Sugar Pine stump, 34-inch diameter, containing scribed BT in opened face bears Record: N16°W, 39.6 feet.

I marked new trees CS-BT and took measurements to center of trees at lower blaze:

- A White Fir, 19-inch diameter, bears S39°W, 30.4 feet.
- A Cedar, 14-inch diameter, bears N42°W, 40.1 feet.

October 24, 1973  
B. Malotte  
R. Frost

Approved by: Edward McGinty  
County Surveyor