

## FIRST RE-ESTABLISHMENT

GCDB 640600

Quarter corner common to Sections 1 and 12, Township 39 South, Range 3 East, W.M.  $V = 19\frac{1}{2}^\circ$

Found a 1-inch pipe, exposed 12 inches, from which:

- An original BT, now a 44-inch diameter Fir snag with opened upper blaze, and the scribe "¼S" visible, bears  $S43^\circ W$ , 15.8 feet to face of blaze.
- Nail with "W" stamped on the head is driven into the lower blaze.
- 24-inch Fir, dead, with axe work and healed and opened blazes, bears  $N59^\circ W$ , 8.9 feet to face of lower blaze.
- Nail with "W" stamped on the head is driven into the lower blaze.

I replaced the found pipe with a 1 x 36-inch Galvanized iron pipe, exposed 5 inches with a 2½-inch bronze disc marked:

Jackson County 1976  
T39S R3E  
1  
—  
12

I marked the following trees CS BT and took measurements to the center of tree at the lower blaze:

- White Fir, 5 inches in diameter, bears  $S01^\circ W$ , 128.1 feet.

I mounded stone around the corner and stuck the found pipe loosely into the ground, at an angle, along the mound.

The corner lies about 100 feet North of a washed out old road.

September 22, 1976  
R. Roberts  
E. Graham

Approved by: Edward McGinty  
County Surveyor