

FIRST RE-ESTABLISHMENT

GCDB 700200

Section corner common to Sections 25 and 36, Township 39 South, Range 3 East, and Sections 30 and 31, Township 39 South, Range 4 East, W.M. $V = 15^\circ$

Found 5/8-inch diameter steel rod projecting 5 inches in a pile of stones, with an aluminum cap marked:

WEYERHAEUSER
R3,R4
25 | 30

36 | 31
1973
T39S
ORLS 686

I replaced said rod with a 1 x 36-inch Galvanized iron pipe set 32 inches in the ground with a 2½-inch bronze disc marked:

T39S
R3E R4E
S25 | S30

S36 | S31
C.S.
1973

From which:

Original BTs found as follows:

- A double trunked Fir snag, 29-inch diameter, containing scribed "SR" in partially opened face bears, $S48^\circ W$, 33.08 feet to scribed face. Record: $S42^\circ W$, 33.0 feet.
- A Fir, 28-inch diameter, containing scribed "5" in partially open face, bears $N64^\circ W$, 43.29 feet to scribed face.
- Stump holes found at record location of NE and SE BTs.

I marked the following trees CS BT and took measurements to center of trees at lower blaze:

- A Sugar Pine, 15-inch diameter, bears $N79^\circ E$, 52.4 feet.
- A White Fir, 20-inch diameter, bears $S17^\circ E$, 35.9 feet.
- A Cedar, 9-inch diameter, bears $S16\frac{1}{2}^\circ W$, 56.2 feet.
- A Douglas Fir, 11-inch diameter, bears $N20\frac{1}{2}^\circ W$, 47.8 feet.
- A Found cooper-nickel pipe, ½-inch diameter projecting 9 inches bears West, 0.5 feet.

Corner lies approximately 270 feet West of location marker alongside Road

October 5, 1973
B. Malotte
R. Frost

Approved by: Edward McGinty
County Surveyor