

## FIRST RE-ESTABLISHMENT

GCDB 700240

Quarter corner common to Sections 25 and 30, Township 39 South, Range 3 and 4 East, W.M.  
 $V = 21\frac{1}{2}^\circ$

Found original NE BT, a Cedar now 19-inch diameter, with partially open face, at record bearing and distance,  $N79^\circ E$ , 20.46 feet to exposed face.

I set a 1 x 36-inch Galvanized iron pipe in a found pile of stone 32 inches in the ground with a 2½-inch bronze disc marked:

T39S  
¼S  
R3E R4E  
25 | 30  
C.S.  
1973

The stump depression of original NW BT, section of which found alongside containing axed chaining notch and partial scribed "BT" bears Record:  $N45^\circ W$ , 21.12 feet.

I marked new trees CS BT:

- A White Fir, 18-inch diameter, bears  $N46\frac{1}{2}^\circ E$ , 35.0 feet to center of tree at lower blaze.
- A Sugar Pine, 16-inch diameter, bears  $N73^\circ W$ , 25.2 feet to center of tree at lower blaze.

October 5, 1973  
B. Malotte  
R. Frost

Approved by: Edward McGinty  
County Surveyor

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

## SECOND RE-ESTABLISHMENT

GCDB 700240

Quarter corner common to sections 25 and 30, Township 39 South, Range 3 and 4 East, W.M.  
Found a 2 ½ ins. diam. brass cap in a small mound of stone MKD:

T39S  
¼S  
R3E R4E  
25|30  
C.S.  
1973

### Bearing Trees Found:

- 24 ins. diam. Cedar with single healed blaze, Brs: N79°E, 20.55 ft. (record: N79°E, 20.46 ft.)
- Sugar pine, dead and down not re-measured.

### New Bearing Trees:

- 14 ins. diam. Cedar with upper blaze "CS", lower blaze "BT", Brs: S7°E, 42.05 ft.
- 8 ins. diam. White Fir with upper blaze "BS, lower blaze "BT", Brs: S89°W, 34.45 ft.

Aluminum Nail in a 20 ins. diam. Douglas Fir with line blazes, Brs: North, 1.33 ft. to head of nail.

September 3, 2009

S. Fein  
S. Beecher

Kerry K. Bradshaw  
County Surveyor

V = 18°E  
Book II  
P.- 45