

FIRST RE-ESTABLISHMENT

GCDB 700300

Section corner common to Section 24 and 25, Township 39 South, Range 3 East, and Section 19 and 30, Township 39 South, Range 4 East, W.M.

Found at the corner position, exposed 8 inches and in a mound of stones, the 2½-inch diameter galvanized iron pipe with a 3½-inch diameter brass cap set by the BLM in 1967, marked:

T39S	
R3E	R4E
S24	S19

S25	S30
1967	

Original bearing trees recorded by E.T.T. Fisher of the GLO in 1858, found and measured to center of trees at base:

- Burnt cedar stump bears S81°E, 52.0 feet. Record: S83°E, 51.5 feet.
- Sawed Sugar Pine stump with indiscernible scribe marks in opened upper blaze bears Record: N4°W, 48.2 feet.

Bearing trees recorded by the BLM in 1967 found with healed single blazes and measured to center of trees at base:

- White Fir snag bears N26°E, 20.8 feet. Record: N8½°E.
- White Fir, dead and down bears Record: S82°E, 11.9 feet to center of stump hole.
- White Fir, dead and down bears S35°W, 13.9 feet. Record: S32°W.

Marked new bearing trees "CS" "BT" and took measurements to center of trees at lower blaze:

- White Fir 7-inch diameter bears 28°E, 33.8 feet.
- Douglas Fir 11-inch diameter bears S81¾°W, 41.0 feet.
- Douglas Fir 13-inch diameter bears S9¼°W, 32.9 feet.
- Douglas Fir 12-inch diameter bears S66½°E, 72.3 feet.

Corner lies approximately 250 feet south from power line road.

November 14, 2007

H. Durkee
B. Beeman

Roger R. Roberts
Jackson County Surveyor

P. - 245
V. - 18°15'