

FIRST RE-ESTABLISHMENT

GCDB 700400

Section corner common to Sections 13 and 24, Township 39 South, Range 3 East, and Sections 18 and 19, Township 39 South, Range 4 East, W.M.

At the corner, found projecting 9 inches in mound of stone, 2-inch diameter iron pipe with 3-inch diameter standard BLM brass cap marked:

T39S	
R3E	R4E
S13	S18

S24	S19
1967	

Original bearing trees recorded by S. Truax in 1859, found:

- Sawed Fir stob, 20-inch diameter, containing scribed "T39S" in partially exposed upper face, bears N65°E, 24.2 feet to scribed upper face. Record: 24.42 feet.
- Fir snag, 34-inch diameter, containing scribed "S19" in partially exposed upper face, bears S71°E, 5.10 feet to scribed face. Record: 5.28 feet.
- Sawed Fir stob, 30-inch diameter, with healed blazes, bears Record: S40°W, 36.3 feet to estimated face. Re-measured 36.72 feet to center of tree.
- White Fir, 29-inch diameter, with healed blazes, bears Record: N20°W, 23.76 feet to estimated face. Re-measured 24.13 feet to center of tree.

Marked new trees "CS" "BT" and took measurements to center of trees at lower blaze:

- White Fir, 12-inch diameter, bears N10°E, 8.85 feet.
- White Fir, 11-inch diameter, bears S1°W, 48.15 feet.
- White Fir, 24-inch diameter, bears S21°E, 86.24 feet.

Corner lies about 42 feet West of location marker on 42-inch diameter Fir stump alongside road C. North-South.

August 1, 1983
R. Frost
B. Malotte

Edward McGinty
County Surveyor

V = 18°