

FIRST RE-ESTABLISHMENT

GCDB 700440

Quarter corner common to Section 13, Township 39 South, Range 3 East and Section 18, Township 39 South, Range 4 East, W.M.

At the corner, found projecting 10 inches in mound of stone, 2-inch diameter galvanized iron pipe with 3-inch diameter standard BLM brass cap marked:

T39S
¼
R3E R4E
S13 | S18
1967

An original bearing tree marked by S. Truax in 1859:

- A sawed Fir stob, now 21-inch diameter containing scribed "4" in partially exposed upper face bears N63°E, 11.7 feet to scribed face. Record: 11.88 feet.

Bearing trees marked by the BLM in 1967, found and re-measured to center of trees:

- Sawed Fir stob, 16-inch diameter, scribed "BT" in partially healed single blaze, bears S84°E, 62.6 feet. Record: 62.7 feet.
- White Fir, 15-inch diameter, containing scribe marks in partially exposed single face, bears S79°W, 22.6 feet. Record: S78°W, 22.44 feet.

Marked a new tree "CS" "BT":

- White Fir, 10-inch diameter, bears N6°W, 17.35 feet to center of tree at lower blaze.

Corner lies about 100 feet East of old dirt road C. North-South.

August 2, 1983
R. Frost
B. Malotte

Edward McGinty
County Surveyor

V = 19½°
P.-73