

## FIRST RE-ESTABLISHMENT

GCDB 100100

Section corner common to Section 36, Township 39 South, Range 3 East, Section 1, Township 40 South, Range 3 East, Section 31, Township 39 South, Range 4 East, and Section 6, Township 40 South, Range 4 East, W.M.  $V = 20\frac{1}{2}^\circ$

From the following original evidence and at the location noted below, I set a 1 x 36-inch Galvanized iron pipe in a found pile of stones 24 inches in the ground with a 2½-inch bronze disc marked:

	T39S	
	R3E R4E	
S36	S31	
S 1	S 6	
	T40S	
	C.S.	
	1973	

Original trees marked by E.T.T. Fisher in 1858 found as follows:

- A Cedar, 44-inch diameter, containing scribed "S31" in open face bears  $N1^\circ30'W$ , 71.94 feet to scribed face. Record:  $N1^\circ E$ , 71.94 feet.
- A Cedar, 45-inch diameter, (lower section of tree chopped out) bears record,  $N76^\circ W$ , 52.8 feet from estimated face of tree.
- A burnt Pine stump bears record,  $S25^\circ W$ , 74.58 feet to center.

I marked the following trees CS BT and took measurements to center of tree at lower blaze:

- A Ponderosa Pine, 15-inch diameter bears  $N51^\circ20'E$ , 50.43 feet.
- A Sugar Pine, 18-inch diameter bears  $S44^\circ50'E$ , 39.35 feet.
- A Ponderosa Pine, 14-inch diameter bears  $S14^\circ25'W$ , 44.76 feet.
- A Ponderosa Pine, 21-inch diameter bears  $N43^\circ40'W$ , 34.5 feet.
- A found copper-nickel pipe, ½-inch diameter projecting 12 inches bears  $N64^\circ W$ , 0.87 feet.

Corner lies approximately  $S49^\circ E$ , 228 feet from location marker on 12-inch diameter Fir, at end of jeep road.

October 17, 1973

E. Graham

B. Malotte

R. Frost

Approved by: Edward McGinty

County Surveyor