

## FIRST RE-ESTABLISHMENT

GCDB 100140

Quarter corner common to Section 36, Township 39 South, Range 3 East, and Section 31, Township 39 South, Range 4 East, W.M.  $V = 17\frac{1}{2}^\circ$

Found  $\frac{5}{8}$ -inch diameter, steel rod, in a pile of stone, with an aluminum cap marked:

WEYERHAEUSER  
 $\frac{1}{4}$   
36 | 31  
1973  
ORLS 686

I replaced said rod with a 1 inch x 36-inch Galvanized iron pipe set 28 inches in the ground with a 2½-inch bronze disc marked:

T39S  
 $\frac{1}{4}$ S  
R3E R4E  
36 | 31  
C.S.  
1973

From which:

- An original BT, now a Pine snag, 32-inch diameter approximately 25 feet high, containing scribed " $\frac{1}{4}$ S" bears  $N37^\circ E$ , 20.46 feet to scribed face. Record:  $N36^\circ E$ , 20.46 feet.
- An original BT, now a Pine snag, 36-inch diameter, approximately 15 feet high, containing scribed " $\frac{1}{4}$ S" "T" in opened face bears  $N68^\circ W$ , 12.54 feet to scribed face. Record:  $N67^\circ W$ , 12.54 feet.

I marked the following new trees CS-BT and took measurements to center of trees at lower blaze:

- A Douglas Fir, 10-inch diameter bears  $N58\frac{1}{2}^\circ W$ , 18.7 feet.
- A Douglas Fir, 12-inch diameter bears  $N53^\circ E$ , 34.3 feet.

October 4, 1973  
B. Malotte  
R. Frost

Approved by: Edward McGinty  
County Surveyor