

## FIRST RE-ESTABLISHMENT

GCDB 140300

Quarter corner common to Section 19 and 30, Township 39 South, Range 4 East, W.M.  $V = 20^\circ$

Found, 3/4 x 42-inch copper-nickle pipe in mound of stone.

I replaced said pipe with a 1 x 36-inch Galvanized iron pipe 28 inches in the ground with a 2½-inch bronze disc marked:

Jackson County 1975  
T39S R4E  
¼S 19  
—  
30

Original BTs marked by S. Truax in 1859, found as follows:

- Burned Pine snag, 27-inch diameter, 14 feet high, scribed "¼" in exposed face bears  $S25^\circ E$ , 30.18 feet to scribed face. Record  $S25^\circ E$ , 29.70 feet.
- Pine, 46-inch diameter, scribed "4S" in exposed face bears Record:  $N38^\circ W$ , 44.88 feet.
- Both original trees have "W" nails in base.

I deposited found C-N pipe alongside corner, marked new trees CS BT and took measurements to center of trees at lower blaze:

- Douglas Fir, 14-inch diameter bears  $N38^\circ E$ , 13.21 feet.
- Douglas Fir, 9-inch diameter bears  $S28^\circ E$ , 22.84 feet.

Corner lies on West slope, on blazed East-West line, about 350 feet East of location marker on 8-inch diameter Red Fir, alongside road.

August 11, 1975  
B. Malotte  
R. Frost

Approved by: Edward McGinty  
County Surveyor